# SAFETY DATA SHEET



#### 1. Identification

Product identifier AKWASEAL® FLEX

Other means of identification None.

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name
Address
CETCO, an MTI Company
2870 Forbs Avenue
Hoffman Estates, IL 60192

United States

**Telephone** General Information 800 527-9948

Website http://www.cetco.com/

E-mail safetydata@mineralstech.com

**Emergency phone number** Emergency 1.866.519.4752/1 760 476 3962

**Americas** 1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962

# 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A
Sensitization, respiratory Category 1
Sensitization, skin Category 1
Carcinogenicity Category 2

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Category 2

Specific target organ toxicity, repeated

exposure

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May

cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonged or

repeated exposure.

**Precautionary statement** 

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate

ventilation wear respiratory protection.

**Response** If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable

for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing. If exposed or concerned: Get medical

advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison

center/doctor. Take off contaminated clothing and wash it before reuse.

Material name: AKWASEAL® FLEX

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

25% of the mixture consists of component(s) of unknown acute oral toxicity. 62.5% of the mixture consists of component(s) of unknown acute dermal toxicity. 62.5% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 25% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
DIBUTYL MALEATE	·	105-76-0	25 - < 50
4,4-Methylenediphenyl Diisocyanate		101-68-8	10 - < 25
4,4'-METHYLENEDIPHENYL DIISOCYANATE, OLIGOMERS		25686-28-6	5 - < 10
1,1'-Methylenebis (isocyanato-) benzene		26447-40-5	< 1
Other components below reportable le	evels		30 - < 40

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a poison center or

doctor/physician.

**Skin contact** Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause

chronic effects.

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Powder. Carbon dioxide (CO2).

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting Move containers from fire area if you can do so without risk.

equipment/instructions Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

**General fire hazards**No unusual fire or explosion hazards noted.

Material name: AKWASEAL® FLEX

SDS US

#### Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in tightly closed container. Store in a well-ventilated place. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

## Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL. TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

IIS OSHA Table	7-1 Limits for	Air Contaminants	(29 CFR 191	0.1000)
US. USITA Table	; <b>Z</b> -1 LIIIIII 101 /	Ali Gullallillallis i	(23 GFR 131	0.1000)

Components	Туре `	Value	
4,4-Methylenediphenyl Diisocyanate (CAS 101-68-8)	Ceiling	0.2 mg/m3	
		0.02 ppm	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	
4,4-Methylenediphenyl Diisocyanate (CAS 101-68-8)	TWA	0.005 ppm	

US. NIOSH: Pocket Guide to Che	SH: Pocket Guide to Chemical Hazards		
Components	Туре	Value	
4,4-Methylenediphenyl Diisocyanate (CAS 101-68-8)	Ceiling	0.2 mg/m3	
		0.02 ppm	
	TWA	0.05 mg/m3	

**Biological limit values** Appropriate engineering controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. General ventilation normally adequate. Provide eyewash station and safety shower.

0.005 ppm

#### Individual protection measures, such as personal protective equipment

Applicable for industrial settings only. Chemical respirator with organic vapor cartridge and full Eye/face protection facepiece.

Material name: AKWASEAL® FLEX 16171 Version #: 02 Revision date: 06-May-2020 Issue date: 06-May-2020 Skin protection

Hand protection Applicable for industrial settings only. Wear appropriate chemical resistant gloves.

Applicable for industrial settings only. Wear appropriate chemical resistant clothing. Use of an Other

impervious apron is recommended.

Applicable for industrial settings only. Chemical respirator with organic vapor cartridge and full Respiratory protection

facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

**Appearance** 

Physical state Liquid. Liquid. **Form** 

Color Cloudy. Colorless. Yellow.

Odor Not available. **Odor threshold** Not available. pН Not available.

98.6 °F (37 °C) estimated Melting point/freezing point

Initial boiling point and boiling Not available.

range

Flash point 199.9 °F (93.3 °C) Pensky-Martens Closed Cup estimated

Not available. **Evaporation rate** Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%)

0.0006 hPa estimated Vapor pressure

Vapor density Not available. 1.055 estimated Relative density

Solubility(ies)

Solubility (water) **INSOLUBLE** Partition coefficient Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** 

Viscosity 400 - 600 mPa·s estimated

Other information

1.20 g/cm3 estimated Density

**Explosive properties** Not explosive.

Combustible IIIB estimated Flammability class

Not oxidizing. Oxidizing properties Specific gravity 1.2 estimated

#### 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability** 

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials.

Acids. Alcohols.

Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

## 11. Toxicological information

#### Information on likely routes of exposure

May cause irritation to the respiratory system. May cause allergy or asthma symptoms or Inhalation

breathing difficulties if inhaled. Prolonged inhalation may be harmful.

Causes skin irritation. May cause an allergic skin reaction. Skin contact

Causes serious eye irritation. Eye contact

Expected to be a low ingestion hazard. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness

and pain. May cause an allergic skin reaction. Dermatitis. Rash.

## Information on toxicological effects

**Acute toxicity** Not known.

Components **Species Test Results** 

1,1'-Methylenebis (isocyanato-) benzene (CAS 26447-40-5)

**Acute Dermal** 

LD50 Rabbit 6200 mg/kg

Inhalation

LC50 Rat 0.369 mg/l/4h

4,4-Methylenediphenyl Diisocyanate (CAS 101-68-8)

**Acute** 

Inhalation

LC50 Rat 0.369 mg/l, 4 Hours

Skin corrosion/irritation

Serious eve damage/eve

irritation

Causes skin irritation. Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

1.1'-Methylenebis (isocyanato-) benzene 3 Not classifiable as to carcinogenicity to humans.

(CAS 26447-40-5)

4,4-Methylenediphenyl Diisocyanate (CAS 101-68-8) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

#### US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard** Not an aspiration hazard.

Material name: AKWASEAL® FLEX

**Chronic effects** Prolonged inhalation may be harmful. May cause damage to organs through prolonged or

repeated exposure.

## 12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity** 

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

No data is available on the degradability of any ingredients in the mixture. Persistence and degradability

No data available. Bioaccumulative potential No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

## 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not established.

the IBC Code

## 15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication US federal regulations

Standard, 29 CFR 1910.1200.

#### **Toxic Substances Control Act (TSCA)**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### TSCA Chemical Action Plans, Chemicals of Concern

Methylene Diphenyl Diisocyanate (MDI) And Related Compounds 1,1'-Methylenebis (isocyanato-) benzene

Action Plan [RIN 2070-ZA15] (CAS 26447-40-5)

Methylene Diphenyl Diisocyanate (MDI) And Related Compounds 4,4-Methylenediphenyl Diisocyanate (CAS 101-68-8)

Action Plan [RIN 2070-ZA15]

4,4'-METHYLENEDIPHENYL DIISOCYANATE, Methylene Diphenyl Diisocyanate (MDI) And Related Compounds

OLIGOMERS (CAS 25686-28-6) Action Plan [RIN 2070-ZA15]

# CERCLA Hazardous Substance List (40 CFR 302.4)

4,4-Methylenediphenyl Diisocyanate (CAS 101-68-8) Listed.

## SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

# SARA 302 Extremely hazardous substance

Not listed.

Material name: AKWASEAL® FLEX SDS US chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
4,4-Methylenediphenyl Diisocyanate	101-68-8	10 - < 25	

## Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

4,4-Methylenediphenyl Diisocyanate (CAS 101-68-8)

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

#### **US state regulations**

#### California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

- 1,1'-Methylenebis (isocyanato-) benzene (CAS 26447-40-5)
- 4,4-Methylenediphenyl Diisocyanate (CAS 101-68-8)

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date06-May-2020Revision date06-May-2020

Version # 02

HMIS® ratings Health: 2\*

Flammability: 0 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 0
Instability: 0

Material name: AKWASEAL® FLEX

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and completeness of such information for each particular use. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. CETCO, an MTI Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

**Revision information** 

Product and Company Identification: Alternate Trade Names