SAFETY DATA SHEET



1. Identification

Product identifier CETGUARD TOPCOAT W

Other means of identification None.

Recommended use Not available. Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name CETCO, an MTI Company **Address** 2870 Forbs Avenue Hoffman Estates, IL 60192

United States

General Information **Telephone** 800 527-9948

Website http://www.cetco.com/

E-mail safetydata@mineralstech.com

Emergency phone number Emergency 1.866.519.4752/1 760 476 3962

1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962 **Americas**

2. Hazard(s) identification

Physical hazards Flammable liquids Category 2 Health hazards Skin corrosion/irritation Category 2 Sensitization, skin Category 1

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction.

May cause respiratory irritation.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear

protective gloves/eye protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison

center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to

extinguish.

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Storage

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal**

Hazard(s) not otherwise

classified (HNOC)

None known.

Material name: CETGUARD TOPCOAT W 1/9 16036 Version #: 04 Revision date: 21-April-2020 Issue date: 26-February-2018

1.3% of the mixture consists of component(s) of unknown acute dermal toxicity. % of the mixture consists of component(s) of unknown acute inhalation toxicity. 1.3% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 1.3% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Methyl methacrylate		80-62-6	10 - < 50
2-Ethylhexyl acrylate		103-11-7	10 - < 25
TITANIUM DIOXIDE		13463-67-7	0.1 - < 10
Other components below re	eportable levels		60 - < 70
Additional components			
Chemical name	Common name and synonyms	CAS number	%

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Skin contact

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important Direct con

symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). sand Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Use standard firefighting procedures and consider the hazards of other involved materials.

Fire fighting equipment/instructions
Specific methods

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

General fire hazards Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

16036 Version #: 04 Revision date: 21-April-2020 Issue date: 26-February-2018

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep out of the reach of children. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Components	r Contaminants (29 CFR 1910.1000) Type	Value	Form
Methyl methacrylate (CAS 80-62-6)	PEL	410 mg/m3	
		100 ppm	
TITANIUM DIOXIDE (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	
Methyl methacrylate (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
TITANIUM DIOXIDE (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to Cher	mical Hazards		
Components	Туре	Value	
Methyl methacrylate (CAS 80-62-6)	TWA	410 mg/m3	
		100 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Material name: CETGUARD TOPCOAT W

Skin protection

Hand protection Wear appropriate chemical resistant gloves.Other Wear appropriate chemical resistant clothing.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Various.
Odor Ester-like.
Odor threshold Not available.
pH Not available.

Melting point/freezing point -92.2 °F (-69 °C) estimated Initial boiling point and boiling 213.8 °F (101 °C) estimated

range

Flash point 71.6 °F (22.0 °C) DIN EN ISO 3680 estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 1.65 % Explosive limit - upper (%) 12.5 %

Vapor pressure38.7 hPa estimatedVapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not Applicable estimated

Decomposition temperature Not available.

Viscosity 9000 mPa·s EN ISO 2555

Other information

Density 1.17 g/cm3 estimated

Explosive properties Not explosive.

Flammability class Flammable IB estimated

Miscible (water)not miscibleOxidizing propertiesNot oxidizing.Percent volatile17.5 % estimatedSpecific gravity1.17 estimated

VOC 0.1 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Exothermic reaction and Hazardous polymerization can occur. This product may react with

oxidizing agents.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Strong oxidizing agents. Nitrates. Peroxides.

Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

May cause irritation to the respiratory system. Prolonged inhalation may be harmful. Inhalation

Skin contact Causes skin irritation. May cause an allergic skin reaction. Direct contact with eyes may cause temporary irritation. **Eve contact**

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an

allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Components **Species Test Results**

2-Ethylhexyl acrylate (CAS 103-11-7)

Acute

Dermal

LD50 Rabbit 7522 mg/kg

Oral

LD50 Rat 4435 mg/kg

Methyl methacrylate (CAS 80-62-6)

Acute

Dermal

LD50 Rabbit 5000 mg/kg

Inhalation

LC50 Mouse 18.5 mg/l, 2 Hours

> Rat 4632 mg/l/4h

Oral

LD50 Rat 7872 mg/kg

7800 mg/kg

TITANIUM DIOXIDE (CAS 13463-67-7)

Acute

Oral

LD50

Rat 10000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

ACGIH sensitization

METHYL METHACRYLATE (CAS 80-62-6) Dermal sensitization

Not a respiratory sensitizer. Respiratory sensitization

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Risk of cancer cannot be excluded with prolonged exposure. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

2-Ethylhexyl acrylate (CAS 103-11-7) 2B Possibly carcinogenic to humans

Material name: CETGUARD TOPCOAT W 16036 Version #: 04 Revision date: 21-April-2020 Issue date: 26-February-2018 Methyl methacrylate (CAS 80-62-6) TITANIUM DIOXIDE (CAS 13463-67-7) 3 Not classifiable as to carcinogenicity to humans.

2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

May cause respiratory irritation.

Specific target organ toxicity -

single exposure

may cause respiratory initial

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

This product is not expected to cause reproductive or developmental effects.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Test Results Components **Species** 2-Ethylhexyl acrylate (CAS 103-11-7) Aquatic Algae IC50 Algae 44 mg/L, 72 Hours EC50 Daphnia 17.45 mg/L, 48 Hours Crustacea Methyl methacrylate (CAS 80-62-6) Aquatic Crustacea EC50 Daphnia 69 mg/L, 48 Hours Fish LC50 Fathead minnow (Pimephales promelas) 136.3 - 183.4 mg/l, 96 hours Fish 259 mg/L, 96 Hours TITANIUM DIOXIDE (CAS 13463-67-7) Aquatic Crustacea EC50 Water flea (Daphnia magna) > 1000 mg/l, 48 hours

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Mummichog (Fundulus heteroclitus)

Bioaccumulative potential

Fish

Partition coefficient n-octanol / water (log Kow)

Methyl methacrylate 1.38

LC50

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

> 1000 mg/l, 96 hours

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1263

Material name: CETGUARD TOPCOAT W

16036 Version #: 04 Revision date: 21-April-2020 Issue date: 26-February-2018

UN proper shipping name Flammable liquids, n.o.s. (PAINT)

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group III

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN1263 **UN proper shipping name** PAINT

Transport hazard class(es)

Class 3
Subsidiary risk Packing group III
Environmental hazards No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1263 **UN proper shipping name** PAINT

Transport hazard class(es)

Class 3
Subsidiary risk Packing group III
Environmental hazards

Marine pollutant No.

EmS Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Methyl methacrylate (CAS 80-62-6)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Methyl methacrylate	80-62-6	10 - < 50

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Methyl methacrylate (CAS 80-62-6)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

Listed.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Methyl methacrylate (CAS 80-62-6)

Low priority

US state regulations

California Proposition 65



WARNING: This product can expose you to TITANIUM DIOXIDE, which is known to the State of California to

cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

TITANIUM DIOXIDE (CAS 13463-67-7) Listed: September 2, 2011

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2-Ethylhexyl acrylate (CAS 103-11-7) Methyl methacrylate (CAS 80-62-6) TITANIUM DIOXIDE (CAS 13463-67-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Material name: CETGUARD TOPCOAT W

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

26-February-2018 Issue date 21-April-2020 **Revision date**

Version # 04

HMIS® ratings Health: 2*

Flammability: 3 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 3 Instability: 2

The information provided in this Safety Data Sheet is correct to the best of our knowledge, **Disclaimer**

information and belief at the date of its publication. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor

assumes any liability, for its use. It is the user's responsibility to verify the suitability and

completeness of such information for each particular use. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. CETCO, an MTI Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written

based on the best knowledge and experience currently available.

Transport Information: Material Transportation Information **Revision information**

Material name: CETGUARD TOPCOAT W