SAFETY DATA SHEET



1. Identification

Product identifier CIVIL PRO™ 125

Other means of identification None.

Recommended use Not available.

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

Category 1

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name CETCO, an MTI Company Address 2870 Forbs Avenue

Hoffman Estates, IL 60192

United States

Telephone General Information 800 527-9948

Website http://www.cetco.com/

E-mail safetydata@mineralstech.com

Emergency phone number Emergency 1.866.519.4752/1 760 476 3962

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1A

Specific target organ toxicity, repeated

exposure

Environmental hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Keep out of reach of children. Read label before use. Obtain special instructions before use. Do

not handle until all safety precautions have been read and understood. Do not breathe dust. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear

protective gloves/protective clothing/eye protection/face protection.

Response If medical advice is needed, have product container or label at hand. IF exposed or concerned:

Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information 5.96% of the mixture consists of component(s) of unknown acute oral toxicity. 7.95% of the

mixture consists of component(s) of unknown acute dermal toxicity. 7.95% of the mixture consists

of component(s) of unknown acute hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Material name: CIVIL PRO™ 125 SDS CANADA

16099 Version #: 02 Revision date: 07-March-2019 Issue date: 15-August-2018

Chemical name	Common name and synonyms	CAS number	%
SILICA, CRYSTALLINE, QUARTZ		14808-60-7	5 - < 10
SILICA, CRYSTALLINE, CRISTOBALITE		14464-46-1	1 - < 3
Other components below reportable levels			90 - 100

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Occupational Exposure Limits for constituents are listed in Section 8. **Composition comments**

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Prolonged exposure may cause chronic effects.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted. General fire hazards

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

Material name: CIVIL PRO™ 125 SDS CANADA

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	Form
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Canada. Alberta OELs (Occupation	-		
Components	Туре	Value	Form
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles.
Constituents	Туре	Value	Form
TRADE SECRET	TWA	3 mg/m3	Respirable particles.
		10 mg/m3	Total particulate.
Canada. British Columbia OELs. (C Safety Regulation 296/97, as amen		for Chemical Substances, Oc	cupational Health and
Components	Туре	Value	Form
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Constituents	Туре	Value	Form
TRADE SECRET	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Canada. Manitoba OELs (Reg. 217/ Components		nd Health Act) Value	Form
<u> </u>	Туре		
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Canada. Ontario OELs. (Control of Components	Exposure to Biological or Che Type	emical Agents) Value	Form
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction.
Constituents	Туре	Value	Form
TRADE SECRET	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
Canada. Quebec OELs. (Ministry o	f Labor - Regulation respecting	g occupational health and sa	fety)
Components	Туре	Value	Form
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.
Constituents	Туре	Value	Form
TRADE SECRET	TWA	10 mg/m3	Total dust.
Canada. Saskatchewan OELs (Occ	upational Health and Safety R	egulations, 1996, Table 21)	
Components	Туре	Value	Form
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	8 hour	0.05 mg/m3	Respirable fraction.
Constituents	Туре	Value	Form
TRADE SECRET	15 minute	6 mg/m3	Respirable fraction.
		20 mg/m3	Inhalable fraction.
	8 hour	3 mg/m3	Respirable fraction.

Material name: CIVIL PRO™ 125 SDS CANADA

Exposure guidelines Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica

should be monitored and controlled.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Applicable for industrial settings only. Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Applicable for industrial settings only. Use of an impervious apron is recommended. Applicable for industrial settings only. Other

Respiratory protection Use a particulate filter respirator for particulate concentrations exceeding the Occupational

Exposure Limit. Applicable for industrial settings only.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Solid. Physical state **Form** Solid.

Not available. Color Odor Not available. Odor threshold Not applicable.

8.5 - 11 pН

Melting point/freezing point $> 842 \, ^{\circ}\text{F} \, (> 450 \, ^{\circ}\text{C}) \, / \, \text{Not applicable}.$

Initial boiling point and boiling

range

Not applicable.

Flash point Not applicable. **Evaporation rate** Not available. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

Not applicable.

Flammability limit - upper

Not applicable.

(%)

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%) Not applicable. Vapor pressure Vapor density Not applicable. Relative density 2.6 g/cm3

Solubility(ies)

Solubility (water) $< 0.9 \, \text{mg/l}$ **Partition coefficient** Not applicable.

(n-octanol/water)

Auto-ignition temperature Not applicable. > 932 °F (> 500 °C) **Decomposition temperature Viscosity** Not applicable. Viscosity temperature Not applicable.

Other information

Bulk density 0.9 - 1.4 g/cm³ **Explosive limit** Not applicable.

Material name: CIVIL PRO™ 125 SDS CANADA Explosive properties

Explosivity

Not applicable.

Flame extension

Flammability

Flammability (flash back)

Flammability (Heat of combustion)

Flammability (Train fire)

Not explosive.

Not applicable.

Not applicable.

Flammability (Train fire)
Not applicable.
Flammability class
Not applicable.
Not applicable.
Not flammable
UVCB Substance
Molecular formula
Not applicable.
Oxidizing properties
Not oxidizing.

Percent volatile 0 % pH in aqueous solution 8.5 - 11

Specific gravity Not applicable.

VOC 0 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the decomposition temperature. Contact with incompatible materials.

Incompatible materials Powerful oxidizers. Chlorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not known.

Product Species Test Results

CIVIL PRO™ 125

Acute Inhalation

Dust

LC50 Rat > 5.27 mg/l, 4 hr OECD 436

Oral *Dust*

LD50 Rat > 2000 mg/kg OECD 425

Skin corrosion/irritationProlonged skin contact may cause temporary irritation. **Serious eye damage/eye**Direct contact with eyes may cause temporary irritation.

irritation

Material name: CIVIL PRO™ 125

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica

inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory

occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and

respirable crystalline silica should be monitored and controlled.

ACGIH Carcinogens

SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)

A2 Suspected human carcinogen.

Canada - Alberta OELs: Carcinogen category

SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7) Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7) Suspected human carcinogen.

Canada - Quebec OELs: Carcinogen category

SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7) Suspected carcinogenic effect in humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be

harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results
CIVIL PRO™ 125			
Aquatic			
Algae	EC50	Freshwater algae	> 100 mg/l, 72 hours
Crustacea	EC50	Coon stripe shrimp (Pandalus danae)	24.8 mg/l, 96 hours
		Daphnia	> 100 mg/l, 48 hours
		Dungeness or edible crab (Cancer magister)	81.6 mg/l, 96 hours
Fish	LC50	Freshwater fish	16000 mg/l, 96 hours
		Marine water fish	2800 - 3200 mg/l, 24 hours

Persistence and degradability Bioaccumulative potential

No data is available on the degradability of any ingredients in the mixture.

Material name: CIVIL PRO™ 125 SDS CANADA

16099 Version #: 02 Revision date: 07-March-2019 Issue date: 15-August-2018

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS

contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No

Material name: CIVIL PRO™ 125 SDS CANADA

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

TaiwanTaiwan Chemical Substance Inventory (TCSI)NoUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryNo

16. Other information

Issue date15-August-2018Revision date07-March-2019

Version # 02

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and completeness of such information for each particular use. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. CETCO, an MTI Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Material name: CIVIL PRO™ 125 SDS CANADA

16099 Version #: 02 Revision date: 07-March-2019 Issue date: 15-August-2018

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).