SAFETY DATA SHEET



1. Identification

Product identifier DRILL-TERGE™

Other means of identification None.

Recommended use Not available.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name CETCO, an MTI Company Address 2870 Forbs Avenue Hoffman Estates, IL 60192

United States

Telephone General Information 800 527-9948

Website http://www.cetco.com/

E-mail safetydata@mineralstech.com

Emergency phone number Emergency 1.866.519.4752/1 760 476 3962

Americas 1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1
Hazardous to the aquatic environment, acute Category 3

Environmental hazards Hazardous to the aquatic environment, acute Cate

hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye damage. Harmful

to aquatic life.

Precautionary statement

Prevention Wash thoroughly after handling. Do not eat, drink or smoke when using this product.

Contaminated work clothing must not be allowed out of the workplace. Avoid release to the

environment. Wear eye protection/face protection. Wear protective gloves.

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin: Wash with plenty of water. If in

eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs:

Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information 5% of the mixture consists of component(s) of unknown acute dermal toxicity. 5% of the mixture

consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Material name: DRILL-TERGE™

Chemical name	Common name and synonyms	CAS number	%
TRADE SECRET*		Proprietary*	5
Diethanolamine		111-42-2	<0.25
Other components below reportable levels			94.98

Composition comments

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

4. First-aid measures

Inhalation

If gas/fume/vapor/dust/mist from the material is inhaled, remove the affected person immediately to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

General information

media

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated

clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

Dry chemical, CO2, water spray or regular foam. Use methods for the surrounding fire.

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Fire fighting equipment/instructions Specific methods

Move containers from fire area if you can do it without risk. Cool containers with flooding quantities of water until well after fire is out.

Concret fire beneade

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted. This material will not burn.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop leak if you can do so without risk. Flush with plenty of water.

Large Spills: Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. For waste disposal, see section 13 of the SDS.

Environmental precautions

No special environmental precautions required. Contact local authorities in case of spillage to drain/aquatic environment. Prevent discharge of larger quantity to drain.

Material name: DRILL-TERGE™ sps us

7. Handling and storage

Precautions for safe handling

Do not get this material in contact with eyes. Do not taste or swallow. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. Keep away from heat and flame.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS). Keep in a cool, well-ventilated place.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. AC	CGIH	Thres	hold	Limit	Values
--------	------	-------	------	-------	--------

Components	Туре	Value	Form
Diethanolamine (CAS 111-42-2)	TWA	1 mg/m3	Inhalable fraction and vapor.
US. NIOSH: Pocket Guide to Ch	emical Hazards		
Components	Туре	Value	
Diethanolamine (CAS 111-42-2)	TWA	15 mg/m3	
		3 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

Diethanolamine (CAS 111-42-2)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Diethanolamine (CAS 111-42-2)

Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Good general ventilation should be sufficient to control airborne levels. Local exhaust is suggested for use, where possible, in enclosed or confined spaces.

Individual protection measures, such as personal protective equipment

Eye/face protection Applicable for industrial settings only. Wear eye/face protection. Wear safety glasses with side

shields (or goggles) and a face shield. Face shield is recommended.

Skin protection

Hand protection Applicable for industrial settings only. For prolonged or repeated skin contact use suitable

protective gloves. Suitable gloves can be recommended by the glove supplier.

Other Applicable for industrial settings only. Wear suitable protective clothing. Wear appropriate

chemical resistant gloves. Use of an impervious apron is recommended. The use of natural rubber

gloves is recommended.

Respiratory protection Applicable for industrial settings only. In case of insufficient ventilation, wear suitable respiratory

equipment. Not normally needed. If ventilation is not sufficient to effectively prevent buildup of aerosols or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. Use good industrial hygiene practices in handling this material. Eye wash fountain is recommended.

9. Physical and chemical properties

Appearance Clear.
Physical state Liquid.
Form Liquid.

Material name: DRILL-TERGE™ sps us

Color Blue.
Odor Slight.

Odor threshold Not available. pH 8.7 - 9.3

Melting point/freezing point Not available.

Initial boiling point and boiling 212 °F (100 °C)

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Flammability limit - upper Not available.

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.00001 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 1.10 g/cm3 estimated

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Percent volatile 94.98 % estimated

Specific gravity 1.02 VOC CARB

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Stable at normal conditions.

Possibility of hazardous

reactions

products

Will not occur.

Conditions to avoid Contact with incompatible materials. Avoid temperatures above 190°F (87.8°C).

Incompatible materials Peroxides. Phenols. strong acids and strong bases

Hazardous decomposition Upon decomposition, this product may yield oxides of nitrogen and ammonia, carbon dioxide,

carbon monoxide and other low molecular weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

InhalationProlonged inhalation may be harmful.Skin contactMay cause an allergic skin reaction.Eye contactCauses serious eye damage.

Ingestion Harmful if swallowed.

Material name: DRILL-TERGE™ SDS US

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause an allergic skin

reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Harmful if swallowed.

Components Species Test Results

Diethanolamine (CAS 111-42-2)

Acute Oral

LD50 Rat 710 mg/kg

TRADE SECRET

<u>Acute</u> Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritationDue to partial or complete lack of data the classification is not possible.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Due to partial or complete lack of data the classification is not possible.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityDue to partial or complete lack of data the classification is not possible.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Diethanolamine (CAS 111-42-2)

2B Possibly carcinogenic to humans.

TRADE SECRET (CAS Proprietary)

2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityDue to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

repeated exposure

Knowledge about health hazard is incomplete.

Aspiration hazardDue to partial or complete lack of data the classification is not possible.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life. This product is not expected to produce significant ecotoxicity upon

exposure to aquatic organisms and aquatic systems.

Components Species Test Results

Diethanolamine (CAS 111-42-2)

Aquatic

Algae IC50 Algae 7.8 mg/L, 72 Hours
Crustacea EC50 Daphnia 55 mg/L, 48 Hours
Fish LC50 Fathead minnow (Pimephales promelas) 100 mg/l, 96 hours
Fish 4710 mg/L, 96 Hours

Persistence and degradability No data is available

Bioaccumulative potential

No data is available on the degradability of this product.

Partition coefficient n-octanol / water (log Kow)

Diethanolamine -1.43

Mobility in soil No data available.

Material name: DRILL-TERGE™ SDS US

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds,

waterways or ditches with chemical or used container. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Diethanolamine (CAS 111-42-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Diethanolamine (CAS 111-42-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Material name: DRILL-TERGE™ SDS US

US state regulations

California Proposition 65



WARNING: This product can expose you to Diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Diethanolamine (CAS 111-42-2) Listed: June 22, 2012

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Diethanolamine (CAS 111-42-2) TRADE SECRET (CAS Proprietary)

International Inventories

Taiwan

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No

Japan Inventory of Existing and New Chemical Substances (ENCS)

Korea Existing Chemicals List (ECL)

New Zealand

New Zealand Inventory

Philippines

Philippines Philippine Inventory of Chemicals and Chemical Substances

Yes

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Taiwan Chemical Substance Inventory (TCSI)

16. Other information, including date of preparation or last revision

Issue date05-September-2013Revision date20-August-2020

Version # 15

Further information This safety datasheet only contains information relating to safety and does not replace any product

information or product specification.

HMIS® ratings Health: 1

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 1

Flammability: 1
Instability: 0

Material name: DRILL-TERGE™ SDS US

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer

CETCO, an MTI Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and completeness of such information for each particular use.

Third party materials: Insofar as materials not manufactured or supplied by this manufacturer are used in conjunction with, or instead of this product, it is the responsibility of the customer to obtain, from the manufacturer or supplier, all technical data and other properties relating to these and other materials and to obtain all necessary information relating to them. No liability can be accepted in respect of the use of this product in conjunction with materials from another supplier. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the

Revision information

Hazard(s) identification: Response

Disposal considerations: Disposal instructions