SAFETY DATA SHEET



1. Identification

Product identifier SLURRYBOND™

Other means of identification None.

Recommended use Not available.

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name CETCO, an MTI Company Address 2870 Forbs Avenue

Hoffman Estates, IL 60192

United States

Telephone General Information 800 527-9948

Website http://www.cetco.com/

E-mail safetydata@mineralstech.com

Emergency phone number Emergency 1.866.519.4752/1 760 476 3962

Americas 1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1A

Specific target organ toxicity, repeated Category 1

exposure

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information 9.43% of the mixture consists of component(s) of unknown acute dermal toxicity. 9.43% of the

mixture consists of component(s) of unknown acute inhalation toxicity.

3. Composition/information on ingredients

Mixtures

Material name: SLURRYBOND™ sps us

Chemical name	Common name and synonyms	CAS number	%
QUARTZ (SIO2)		14808-60-7	5 - < 10
CRISTOBALITE		14464-46-1	1 - < 3
Oth			00 100

Other components below reportable levels

90 - 100

Composition comments

Occupational Exposure Limits for constituents are listed in Section 8. Occupational Exposure Limits for impurities are listed in Section 8.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists. Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and

delayed

Dusts may irritate the respiratory tract, skin and eyes. Prolonged exposure may cause chronic

effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

During fire, gases hazardous to health may be formed.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

the chemical Special protective equipment

Specific hazards arising from

and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Use water spray to cool unopened containers.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Collect dust using a vacuum cleaner equipped with HEPA filter. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Material name: SLURRYBOND™ SDS US

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits

Components	ts for Air Contaminants (29 CFR 1910.10 Type	Value	Form
CRISTOBALITE (CAS 14464-46-1)	PEL	0.05 mg/m3	Respirable dust.
QUARTZ (SIO2) (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 (29 C			_
Components	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Impurities	Туре	Value	Form
INERT OR NUISANCE DUSTS	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Lin	nit Values		
Components	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide	to Chemical Hazards		
Components	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable dust.
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
logical limit values			
ogioai iiiiii valaoo	No biological exposure limits noted for	the ingredient(s).	
osure guidelines	No biological exposure limits noted for Occupational exposure to nuisance du should be monitored and controlled.	- , ,	espirable crystalline silica
•	Occupational exposure to nuisance du	air changes per hour) should be plicable, use process enclosurain airborne levels below recordshed, maintain airborne levels and to maintain concentrations outable respiratory protection may generate dusts, use	be used. Ventilation rates res, local exhaust ventilation mended exposure limits to an acceptable level. If of dust particulates below must be worn. If material is appropriate local exhaus
osure guidelines propriate engineering trols	Occupational exposure to nuisance du should be monitored and controlled. Good general ventilation (typically 10 should be matched to conditions. If ap or other engineering controls to mainta exposure limits have not been establis engineering measures are not sufficie Occupational Exposure Limit (OEL), s ground, cut, or used in any operation ventilation to keep exposures below thes, such as personal protective equipments.	ust (total and respirable) and re air changes per hour) should be plicable, use process enclosurain airborne levels below recor- shed, maintain airborne levels on to maintain concentrations of uitable respiratory protection in which may generate dusts, use the recommended exposure limitent	be used. Ventilation rates res, local exhaust ventilation mended exposure limits to an acceptable level. If of dust particulates below nust be worn. If material is appropriate local exhausits.
osure guidelines propriate engineering trols	Occupational exposure to nuisance du should be monitored and controlled. Good general ventilation (typically 10 should be matched to conditions. If ap or other engineering controls to mainte exposure limits have not been establis engineering measures are not sufficie Occupational Exposure Limit (OEL), s ground, cut, or used in any operation ventilation to keep exposures below the	ust (total and respirable) and re air changes per hour) should be plicable, use process enclosurain airborne levels below recor- shed, maintain airborne levels on to maintain concentrations of uitable respiratory protection in which may generate dusts, use the recommended exposure limitent	be used. Ventilation rates res, local exhaust ventilation mended exposure limits to an acceptable level. If of dust particulates below nust be worn. If material is appropriate local exhausits.
osure guidelines propriate engineering trols	Occupational exposure to nuisance du should be monitored and controlled. Good general ventilation (typically 10 should be matched to conditions. If ap or other engineering controls to mainta exposure limits have not been establis engineering measures are not sufficie Occupational Exposure Limit (OEL), s ground, cut, or used in any operation ventilation to keep exposures below thes, such as personal protective equipments.	air changes per hour) should be plicable, use process enclosurain airborne levels below record thed, maintain airborne levels on to maintain concentrations outlable respiratory protection in which may generate dusts, use the recommended exposure limitent.	be used. Ventilation rates res, local exhaust ventilat mmended exposure limits to an acceptable level. If dust particulates below hust be worn. If material is appropriate local exhausits.

Material name: SLURRYBOND™ SDS US **Respiratory protection** Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels

exceeding the exposure limits. Chemical respirator with organic vapor cartridge, full facepiece,

dust and mist filter.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid. **Form** Powder. Not available. Color Odor Not available. Odor threshold Not available. Not available. Hq Melting point/freezing point Not available. Not available. Initial boiling point and boiling

range

Flash point

Evaporation rate

Flammability (solid, gas)

Not available.

Not available.

Not available.

Not available.

Flammability limit - lower

(%)

Flammability limit - upper

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.00001 hPa estimated

Not available.

Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Percent volatile 0 % estimated

VOC CARB

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials.

Incompatible materials Powerful oxidizers. Chlorine.

Material name: SLURRYBOND™

Hazardous decomposition products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. Dust may

irritate respiratory system.

Skin contact Dust or powder may irritate the skin.

Eye contact Dust may irritate the eyes.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Dusts may irritate the respiratory tract, skin and eyes.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

CRISTOBALITE (CAS 14464-46-1)

Acute Oral

LD50 Rat > 22500 mg/kg

Skin corrosion/irritationProlonged skin contact may cause temporary irritation. **Serious eye damage/eye**Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the

overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker

protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and

respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

CRISTOBALITE (CAS 14464-46-1) 1 Carcinogenic to humans. QUARTZ (SIO2) (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

CRISTOBALITE (CAS 14464-46-1) Cancer
QUARTZ (SIO2) (CAS 14808-60-7) Cancer
National Toxical and Program (NTP) Penert on Carcinogens

US. National Toxicology Program (NTP) Report on Carcinogens

CRISTOBALITE (CAS 14464-46-1)

Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

NIADTZ (OLOO) (OAO 14000 00 Z)

QUARTZ (SIO2) (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - Not classified.

single exposure

Siligle exposure

Material name: SLURRYBOND™ sds us

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be

harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

No data available.

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

Not applicable.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

CRISTOBALITE (CAS 14464-46-1)

QUARTZ (SIO2) (CAS 14808-60-7)

CRISTOBALITE (CAS 14464-46-1)

QUARTZ (SIO2) (CAS 14808-60-7)

lung effects

lung effects

CRISTOBALITE (CAS 14464-46-1) immune system effects QUARTZ (SIO2) (CAS 14808-60-7) immune system effects

CRISTOBALITE (CAS 14464-46-1) kidney effects QUARTZ (SIO2) (CAS 14808-60-7) kidney effects

4183 Version #: 13 Revision date: 23-July-2018 Issue date: 14-April-2016

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Inventory name

QUARTZ (SIO2) (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

CRISTOBALITE (CAS 14464-46-1) QUARTZ (SIO2) (CAS 14808-60-7)

International Inventories

New Zealand

Philippines

Country(a) or region

Country(s) or region	inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

Philippine Inventory of Chemicals and Chemical Substances

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

New Zealand Inventory

Issue date14-April-2016Revision date23-July-2018

Version # 13

HMIS® ratings Health: 3*

Flammability: 0 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 0 Instability: 0

Disclaimer CETCO, an MTI Company cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

4183 Version #: 13 Revision date: 23-July-2018 Issue date: 14-April-2016

No

Νo

On inventory (yee/ne)*

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

_			•			
ĸ	CIA	n iı	nta	rm	2ti	nn -

This document has undergone significant changes and should be reviewed in its entirety.

Material name: SLURRYBOND™ sps us