

CETCO® X-TORQUE

DRILLING LUBRICANT

DESCRIPTION

CETCO X-TORQUE is a new generation, environmentally friendly drilling lubricant with enhanced corrosion protection. It is a concentrated aqueous solution that mixes well in most water types and is capable of delivering superior performance at lower dosages than competitive products.

RECOMMENDED USE

CETCO X-TORQUE is designed for use in most drilling and boring applications such as HDD and Mineral Exploration.

CHARACTERISTICS

- Appearance: Amber Liquid
- Flash Point: >150 °C
- Specific Gravity: ~0.90
- Unequaled torque reduction at lower dosages.
- Environmentally friendly/readily biodegradable
- Increases penetration rates, protects & extends bit life and mud motors
- Very good corrosion protection
- Excellent mixing properties & synergies with other drilling fluid additives

MIXING AND APPLICATION

Typical dosages range from approximately 0.25% - 0.5% of fluid volume, however dosages of up to 1.0% can be used in extreme circumstances for improved penetration rates and torque reduction. It is recommended to pre-treat the system initially and simply maintain an established dosage rate throughout the drilling operation.

PACKAGING

25 L pail, 200 L drums, and 1000 L IBC

Australia: +61 73719 3500 | www.CETCO.com

UPDATED: JANUARY 2020

© 2020 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

