

# REL-PAC® XTRA-LOW

## DRY POLYANIONIC CELLULOSIC POLYMER

### DESCRIPTION

REL-PAC XTRA-LOW is a low viscosity, non-fermenting dry polymer designed for use as a more efficient filtration control additive in a variety of drilling fluid applications. Intended for use in bentonite and polymer fluids.

### RECOMMENDED USE

REL-PAC XTRA-LOW will help increase borehole stability by lowering filtrate and fluid loss more effectively than other PAC's. REL-PAC XTRA-LOW aids cleaning by not significantly raising viscosities and impeding flow. Helps control reactive formations by reducing available water and controls unconsolidated formations by reducing whole fluid loss.

### CHARACTERISTICS

- For use in fresh and saltwater systems
- Highly dispersible
- Only moderate viscosity increase for increased flow
- Stabilizes many types of drilled formations

### MIXING AND APPLICATION

Mix at high shear through a venturi hopper to avoid fish eyes, clumping and to avoid waste. Add 0.5 kg to 2.0 kg of REL-PAC XTRA-LOW per 1000 L of existing bentonite drilling fluid for hole stabilization.

### PACKAGING

25 kg bags

Australia: +61 73719 3500 | [www.CETCO.com](http://www.CETCO.com)

UPDATED: JANUARY 2020

© 2020 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit [www.CETCO.com](http://www.CETCO.com). CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

