CETCO[®] JOINT COMPOUND

DESCRIPTION

CETCO JOINT COMPOUND is a lead-free, premium grade tool joint and drill collar lubricant for heavy duty drilling. This special mixture of the finest blend of copper flakes with a superior base gives maximum protection under extreme temperature and adverse conditions.

RECOMMENDED USE

CETCO JOINT COMPOUND may be used for drill pipe, drill collars, subsurface drilling tools, tubing, and casing. CETCO JOINT COMPOUND is recommended for use on rotary connections and is designed for drilling hard formations, deep holes, and other high torque applications. Special applications include a breaking-in lubricant for new tool joints and a premium lubricant for the legs of jack-up rigs.

CHARACTERISTICS

- Contains corrosion and H₂S inhibitors
- Eliminates galling and seizing
- Excellent lubricity
- High temperature performance (0°F to 400°F)
- Lead-free
- Meets requirements for tough drilling conditions
- Non-flammable

MIXING AND APPLICATION

Apply liberally.

PACKAGING

20 LB (9 kg) pail, 60 per pallet. All pallets are plastic-wrapped.

North America: 847.851.1800 | 800.527.9948 | www.CETCO.com

UPDATED: MAY 2024

© 2024 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.