## **SAFETY DATA SHEET**



#### 1. Identification

Product identifier SUPER LIG™

Other means of identification

**CAS number** 1415-93-6

Synonyms HUMIC ACID \* LEONARDITE

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name American Colloid Company

Address 2870 Forbs Avenue

Hoffman Estates, IL 60192

**United States** 

**Telephone** General Information 800 426 5564

Website www.colloid.com

E-mail safetydata@mineralstech.com

Emergency phone number +18665194752(US,Ca,Mex) +1 760 476 3962 Access 333562

**Americas** 1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1A

Specific target organ toxicity, repeated Category 1

exposure

Environmental hazards Not classified.

OSHA defined hazards Combustible dust

Label elements



Signal word Danger

Hazard statement May form combustible dust concentrations in air. May cause cancer. Causes damage to organs

through prolonged or repeated exposure.

**Precautionary statement** 

**Prevention** Do not handle until all safety precautions have been read and understood. Prevent dust

accumulation to minimize explosion hazard. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye

protection/face protection. Observe good industrial hygiene practices.

Response If exposed or concerned: Get medical advice/attention. Take off contaminated clothing and wash

before reuse. In case of fire: Use appropriate media to extinguish.

**Storage** Store in accordance with local/regional/national regulations.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

Material name: SUPER LIG™

#### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
QUARTZ	CRYSTALLINE SILICA, QUARTZ SILICA (QUARTZ)	14808-60-7	<6
CRISTOBALITE		14464-46-1	<2
Other components below re	eportable levels		92

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Composition comments

Occupational Exposure Limits for constituents are listed in Section 8. The purity of the product is

100% w/w. Impurities are not applicable for a UVCB substance.

#### 4. First-aid measures

Move to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Inhalation

Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Do not rub eyes. Flush eyes with water as a precaution. Get medical attention if irritation develops Eye contact

and persists.

effects.

If ingestion of a large amount does occur, seek medical attention. No need for first aid is Ingestion

anticipated if material is swallowed.

Most important symptoms/effects, acute and

delayed

Indication of immediate

medical attention and special treatment needed

**General information** 

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Dusts may irritate the respiratory tract, skin and eyes. Prolonged exposure may cause chronic

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s)

involved, and take precautions to protect themselves.

## 5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Dry chemical, CO2, water spray or regular foam. Apply extinguishing media carefully to avoid creating airborne dust. Use any media suitable for the surrounding fires. Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.

Unsuitable extinguishing media

Specific hazards arising from

the chemical

Explosion hazard: Avoid generating dust; fine dust dispersed in air in sufficient concentrations and in the presence of an ignition source is a potential dust explosion hazard. During fire, gases hazardous to health may be formed.

Do not use water jet as an extinguisher, as this will spread the fire.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. General fire hazards May form combustible dust concentrations in air.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Use only non-sparking tools. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Wear appropriate protective equipment and clothing during clean-up. Wear a dust mask if dust is generated above exposure limits. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: SUPER LIG™ SDS US

# Methods and materials for containment and cleaning up

Eliminate all sources of ignition or flammables that may come into contact with a spill of this material. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Collect dust or particulates using a vacuum cleaner with a HEPA filter. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Flush area with water to remove trace residue. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

### **Environmental precautions**

Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

### 7. Handling and storage

#### Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Avoid significant deposits of material, especially on horizontal surfaces, which may become airborne and form combustible dust clouds and may contribute to secondary explosions. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Explosion-proof general and local exhaust ventilation. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. In case of insufficient ventilation, wear suitable respiratory equipment. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Keep this product from heat, sparks, or open flame.

Conditions for safe storage, including any incompatibilities

Keep the container dry. Keep containers tightly closed in a dry, cool and well-ventilated place. Guard against dust accumulation of this material. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS). Keep in a cool, well-ventilated place.

## 8. Exposure controls/personal protection

US OSUA Table 7.4 Limits for Air Conteminants (20 CED 4040 4000)

#### Occupational exposure limits

Components	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	PEL	0.05 mg/m3	Respirable dust.
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 (29 CFR 1910.	1000)		
Components	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Constituents	Туре	Value	Form
INERT OR NUISANCE DUSTS (CAS SEQ250)	TWA	5 mg/m3	Respirable fraction
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction

Material name: SUPER LIG™ SDS US

**US. NIOSH: Pocket Guide to Chemical Hazards Form** Value Components Type CRISTOBALITE (CAS TWA 0.05 mg/m3 Respirable dust. 14464-46-1) QUARTZ (CAS 14808-60-7) **TWA** 0.05 mg/m3 Respirable dust.

**Biological limit values** No biological exposure limits noted for the ingredient(s).

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica **Exposure guidelines** 

should be monitored and controlled.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. If engineering measures are not sufficient to maintain concentrations of dust particulates below the OEL, suitable respiratory protection must be worn. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Wear dust goggles. Eye wash fountain is recommended. Eye/face protection

Skin protection

Wear appropriate chemical resistant gloves. Hand protection

Wear suitable protective clothing. Use of an impervious apron is recommended. Other

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Use good industrial hygiene practices in handling this material.

## 9. Physical and chemical properties

**Appearance** 

Physical state Solid. **Form** Powder.

Brown to black. Color Odor Not available. **Odor threshold** Not available. Not available. Not available. Melting point/freezing point Initial boiling point and boiling Not available.

range

Non-flammable Flash point **Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

Not available.

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

0.00001 hPa estimated Vapor pressure

Vapor density Not available. Relative density Not available.

Solubility(ies)

Not available. Solubility (water)

Material name: SUPER LIG™ SDS US Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Concentration Combustible Content (wt.%) 71% Rep FAI14-0089B Sample Moisture content 2.1% Mean Particle

size 26 micron

**Dust explosion properties** 

Pmax 6.6 bar +/-10% Rep FAI14-0089B Kst 75 bar.m/s +/-20% Rep FAI14-0089B

Minimum explosible concentration (MEC)

125 - 150 g/m3 MECest=136 Rep FAI14-0089B

Minimum ignition energy (MIE) - dust

> 1000 mJ (with inductance) test equipment maximum Rep FAI14-0089B

cloud

Minimum ignition temperature (MIT) - dust cloud

968 °F (520 °C) Rep FAI14-0089B

**Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing.

VOC CARB

## 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Stable at normal conditions.

Possibility of hazardous

reactions

Will not occur.

Conditions to avoid Keep away from heat, sparks and open flame. High temperatures. Contact with incompatible

materials. Minimize dust generation and accumulation.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Upon decomposition, this product emits oxides of sulfur, carbon monoxide, carbon dioxide and/or

low molecular weight hydrocarbons.

## 11. Toxicological information

Information on likely routes of exposure

InhalationNo adverse effects due to inhalation are expected.Skin contactNo adverse effects due to skin contact are expected.Eye contactDirect contact with eyes may cause temporary irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Dusts may irritate the respiratory tract, skin and eyes.

#### Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

CRISTOBALITE (CAS 14464-46-1)

Acute Oral

LD50 Rat > 22500 mg/kg

QUARTZ (CAS 14808-60-7)

**Acute** 

Oral

LD50 Rat 500 mg/kg

Material name: SUPER LIG™ sds us

Skin corrosion/irritation

Serious eye damage/eye

irritation

Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Not a respiratory sensitizer. Respiratory sensitization

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

May cause cancer. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

CRISTOBALITE (CAS 14464-46-1) 1 Carcinogenic to humans. QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) CRISTOBALITE (CAS 14464-46-1) **US. National Toxicology Program (NTP) Report on Carcinogens** 

CRISTOBALITE (CAS 14464-46-1) Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity single exposure

Not classified.

Specific target organ toxicity repeated exposure

Causes damage to organs through prolonged or repeated exposure.

**Aspiration hazard** Not an aspiration hazard.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica **Chronic effects** 

inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)

In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)

According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Causes damage to organs through prolonged or repeated exposure. Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

## 12. Ecological information

This material is not expected to be harmful to aquatic life. **Ecotoxicity** 

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential No data available. No data available. Mobility in soil

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions** 

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Material name: SUPER LIG™ SDS US 6/9 Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

## 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to

Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

#### 15. Regulatory information

**US** federal regulations

OSHA Process Safety Standard: This material is not known to be hazardous by the OSHA Highly

Hazardous Process Safety Standard, 29 CFR 1910.119.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

#### **Toxic Substances Control Act (TSCA)**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### **CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

CRISTOBALITE (CAS 14464-46-1)

Cancer lung effects

immune system effects

kidney effects

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

#### SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Contains component(s) regulated under the Safe Drinking Water Act.

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer.

## **California Proposition 65**



WARNING: This product can expose you to QUARTZ, which is known to the State of California to cause

cancer. For more information go to www.P65Warnings.ca.gov.

#### California Proposition 65 - CRT: Listed date/Carcinogenic substance

QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

Material name: SUPER LIG™ sps us

#### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

CRISTOBALITE (CAS 14464-46-1) QUARTZ (CAS 14808-60-7)

#### **International Inventories**

Taiwan

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Taiwan Chemical Substance Inventory (TCSI) United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes \*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

## 16. Other information, including date of preparation or last revision

15-March-2021 Issue date 15-March-2021 **Revision date** 

Version #

**Further information** This safety datasheet only contains information relating to safety and does not replace any product

> information or product specification. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate

Solids, for safe handling.

Health: 3\* **HMIS®** ratings

Flammability: 2 Physical hazard: 0

Health: 2 NFPA ratings

Flammability: 2 Instability: 0

UVCB = a substance of Unknown or Variable composition, Complex reaction products or List of abbreviations

Biological materials

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The manufacturer expressly does not make any representations, warranties, or quarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and completeness of such information for each particular use.

Third party materials: Insofar as materials not manufactured or supplied by this manufacturer are used in conjunction with, or instead of this product, it is the responsibility of the customer to obtain. from the manufacturer or supplier, all technical data and other properties relating to these and other materials and to obtain all necessary information relating to them. No liability can be accepted in respect of the use of this product in conjunction with materials from another supplier. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. American Colloid Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

4009 Version #: 31 Revision date: 15-March-2021 Issue date: 15-March-2021

No

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**Revision information** 

Product and Company Identification: Alternate Trade Names

Material name: SUPER LIG™