SAFETY DATA SHEET



1. Identification

Product identifier CORETEX™

Other means of identification None.

Recommended use Not available.

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name CETCO, an MTI Company Address 2870 Forbs Avenue

Hoffman Estates, IL 60192

United States

Telephone General Information 800 527-9948

Website http://www.cetco.com/

E-mail safetydata@mineralstech.com

Emergency phone number Emergency 1.866.519.4752/1 760 476 3962

Americas 1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1A

Specific target organ toxicity, repeated Category 1

exposure

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information 74% of the mixture consists of component(s) of unknown acute oral toxicity. 100% of the mixture

consists of component(s) of unknown acute dermal toxicity. 100% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 100% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Material name: CORETEX™ SDS US

Chemical name	Common name and synonyms	CAS number	%
CORETEX™		Mixture	100
Constituents			
Chemical name	Common name and synonyms	CAS number	%
QUARTZ	CRYSTALLINE SILICA, QUARTZ SILICA (QUARTZ)	14808-60-7	<= 4
CRISTOBALITE		14464-46-1	<= 1.4

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Composition comments Occupational Exposure Limits for constituents are listed in Section 8. Occupational Exposure

Limits for impurities are listed in Section 8.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Prolonged exposure may cause chronic effects.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

General information IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice

(show the label where possible).

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Material can be slippery when wet.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. No unusual fire or explosion hazards noted. General fire hazards

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Material can be slippery when wet. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up This product is miscible in water. Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

Material name: CORETEX™ SDS US

8. Exposure controls/personal protection

Occupational exposure limits

Constituents	for Air Contaminants (29 CFR 1910.1000) Type	Value	Form
CRISTOBALITE (CAS 14464-46-1)	PEL	0.05 mg/m3	Respirable dust.
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 (29 CFF Constituents	R 1910.1000) Type	Value	Form
CRISTOBALITE (CAS	TWA	0.05 mg/m3	Respirable.
14464-46-1)		1.2 mppcf	Respirable.
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable.
(=====,		2.4 mppcf	Respirable.
Impurities	Туре	Value	Form
TRADE SECRET	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit	Values		·
Constituents	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to Constituents	Chemical Hazards Type	Value	Form
CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable dust.
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
logical limit values	No biological exposure limits noted for the in-	gredient(s).	
logical limit values propriate engineering atrols	No biological exposure limits noted for the in Good general ventilation (typically 10 air cha should be matched to conditions. If applicabl or other engineering controls to maintain airb exposure limits have not been established, n	inges per hour) should b le, use process enclosus porne levels below recor	es, local exhaust ventilation nmended exposure limits. If
oropriate engineering atrols ividual protection measures,	Good general ventilation (typically 10 air cha should be matched to conditions. If applicabl or other engineering controls to maintain airb exposure limits have not been established, n such as personal protective equipment	nges per hour) should b le, use process enclosu porne levels below recor naintain airborne levels	es, local exhaust ventilation nmended exposure limits. If to an acceptable level.
oropriate engineering atrols	Good general ventilation (typically 10 air cha should be matched to conditions. If applicabl or other engineering controls to maintain airb exposure limits have not been established, n	nges per hour) should b le, use process enclosu porne levels below recor naintain airborne levels	es, local exhaust ventilation nmended exposure limits. If to an acceptable level.
oropriate engineering atrols ividual protection measures,	Good general ventilation (typically 10 air cha should be matched to conditions. If applicabl or other engineering controls to maintain airb exposure limits have not been established, n such as personal protective equipment	nges per hour) should b le, use process enclosu porne levels below recor naintain airborne levels	es, local exhaust ventilation nmended exposure limits. If to an acceptable level.
oropriate engineering atrols ividual protection measures, Eye/face protection Skin protection	Good general ventilation (typically 10 air cha should be matched to conditions. If applicabl or other engineering controls to maintain airb exposure limits have not been established, n such as personal protective equipment If contact is likely, safety glasses with side sh	inges per hour) should be le, use process enclosur porne levels below recornaintain airborne levels nields are recommended	res, local exhaust ventilatior nmended exposure limits. If to an acceptable level.
oropriate engineering atrols ividual protection measures, Eye/face protection Skin protection Hand protection Other	Good general ventilation (typically 10 air cha should be matched to conditions. If applicabl or other engineering controls to maintain airb exposure limits have not been established, n such as personal protective equipment If contact is likely, safety glasses with side should be with the safety glasses with side should be such as personal protective equipment.	inges per hour) should be le, use process enclosur porne levels below recornaintain airborne levels nields are recommended	res, local exhaust ventilation nmended exposure limits. If to an acceptable level.
oropriate engineering atrols ividual protection measures, Eye/face protection Skin protection Hand protection	Good general ventilation (typically 10 air cha should be matched to conditions. If applicabl or other engineering controls to maintain airb exposure limits have not been established, n such as personal protective equipment If contact is likely, safety glasses with side should be well appropriate chemical resistant gloves. Use of an impervious apron is recommended.	inges per hour) should be le, use process enclosur porne levels below recornaintain airborne levels inields are recommended.	res, local exhaust ventilation nmended exposure limits. If to an acceptable level.
oropriate engineering atrols ividual protection measures, Eye/face protection Skin protection Hand protection Other Respiratory protection	Good general ventilation (typically 10 air cha should be matched to conditions. If applicabl or other engineering controls to maintain airb exposure limits have not been established, n such as personal protective equipment. If contact is likely, safety glasses with side should be well appropriate chemical resistant gloves. Use of an impervious apron is recommended in case of insufficient ventilation, wear suitable.	inges per hour) should be le, use process enclosur porne levels below recornaintain airborne levels in hields are recommended by the commended	res, local exhaust ventilation nmended exposure limits. If to an acceptable level.
oropriate engineering atrols ividual protection measures, Eye/face protection Skin protection Hand protection Other Respiratory protection Thermal hazards meral hygiene	Good general ventilation (typically 10 air cha should be matched to conditions. If applicabl or other engineering controls to maintain airbexposure limits have not been established, near such as personal protective equipment. If contact is likely, safety glasses with side should be a such as personal protective equipment. If contact is likely, safety glasses with side should be a such as personal protective equipment. We are appropriate chemical resistant gloves. Use of an impervious apron is recommended. In case of insufficient ventilation, we are suitable wear appropriate thermal protective clothing. Observe any medical surveillance requirement.	inges per hour) should be le, use process enclosur porne levels below recornaintain airborne levels in hields are recommended by the commended	res, local exhaust ventilation nmended exposure limits. If to an acceptable level.
oropriate engineering atrols ividual protection measures, Eye/face protection Skin protection Hand protection Other Respiratory protection Thermal hazards meral hygiene	Good general ventilation (typically 10 air cha should be matched to conditions. If applicabl or other engineering controls to maintain airbexposure limits have not been established, near such as personal protective equipment. If contact is likely, safety glasses with side should be a such as personal protective equipment. If contact is likely, safety glasses with side should be a such as personal protective equipment. We are appropriate chemical resistant gloves. Use of an impervious apron is recommended. In case of insufficient ventilation, we are suitable wear appropriate thermal protective clothing. Observe any medical surveillance requirement.	inges per hour) should be le, use process enclosur porne levels below recornaintain airborne levels in ields are recommended. d. ble respiratory equipment, when necessary.	res, local exhaust ventilation nmended exposure limits. If to an acceptable level.
oropriate engineering atrols ividual protection measures, Eye/face protection Skin protection Hand protection Other Respiratory protection Thermal hazards meral hygiene asiderations Physical and chemical protection	Good general ventilation (typically 10 air cha should be matched to conditions. If applicable or other engineering controls to maintain air exposure limits have not been established, in such as personal protective equipment. If contact is likely, safety glasses with side should be a such as personal protective equipment. If contact is likely, safety glasses with side should be a such as personal protective equipment. Use of an impervious apron is recommended in case of insufficient ventilation, wear suitable. Wear appropriate thermal protective clothing. Observe any medical surveillance requirements.	inges per hour) should be le, use process enclosur porne levels below recornaintain airborne levels in ields are recommended. d. ble respiratory equipment, when necessary.	res, local exhaust ventilation nmended exposure limits. If to an acceptable level.
oropriate engineering atrols ividual protection measures, Eye/face protection Skin protection Hand protection Other Respiratory protection Thermal hazards meral hygiene asiderations Physical and chemical poearance	Good general ventilation (typically 10 air cha should be matched to conditions. If applicable or other engineering controls to maintain air exposure limits have not been established, in such as personal protective equipment. If contact is likely, safety glasses with side should be a such as personal protective equipment. If contact is likely, safety glasses with side should be a such as personal protective equipment. Use of an impervious apron is recommended. In case of insufficient ventilation, wear suitable wear appropriate thermal protective clothing. Observe any medical surveillance requirement properties. The product consists of bentonite granules be a should be appropriate to the product consists of bentonite granules be a should be appropriate to the product consists of bentonite granules be a should be appropriate to the product consists of bentonite granules be a should be a should be appropriate to the product consists of bentonite granules be a should	inges per hour) should be le, use process enclosur porne levels below recornaintain airborne levels in ields are recommended. d. ble respiratory equipment, when necessary.	res, local exhaust ventilation nmended exposure limits. If to an acceptable level.
oropriate engineering atrols ividual protection measures, Eye/face protection Skin protection Hand protection Other Respiratory protection Thermal hazards meral hygiene asiderations Physical and chemical procearance Physical state	Good general ventilation (typically 10 air cha should be matched to conditions. If applicable or other engineering controls to maintain air exposure limits have not been established, in such as personal protective equipment. If contact is likely, safety glasses with side should be an impervious apron is recommended. In case of insufficient ventilation, wear suitable wear appropriate thermal protective clothing. Observe any medical surveillance requirement or properties. The product consists of bentonite granules be Solid.	inges per hour) should be le, use process enclosur porne levels below recornaintain airborne levels in ields are recommended. d. ble respiratory equipment, when necessary.	res, local exhaust ventilation nmended exposure limits. If to an acceptable level.

Material name: CORETEX™

Odor

Odor threshold

Not available.

Not available.

Not available. pН Not available. Melting point/freezing point Initial boiling point and boiling Not available.

range

Flash point Non-flammable Not available. **Evaporation rate** Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

Non-explosive

(%)

Flammability limit - upper

Not available.

Not available.

(%)

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available. Vapor pressure Not available. Vapor density Not available.

Relative density Solubility(ies)

Negligible Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Viscosity Not available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

VOC **CARB**

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected. Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not known.

Material name: CORETEX™ SDS US Toxicological data

Constituents Species Test Results

CRISTOBALITE (CAS 14464-46-1)

Acute Oral

LD50 Rat > 22500 mg/kg

QUARTZ (CAS 14808-60-7)

Acute Oral

LD50 Rat 500 mg/kg

Skin corrosion/irritation Serious eye damage/eye Prolonged skin contact may cause temporary irritation.

Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded

that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing

regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable

dust and respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

CRISTOBALITE (CAS 14464-46-1) 1 Carcinogenic to humans. QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

CRISTOBALITE (CAS 14464-46-1)

Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

CRISTOBALITE (CAS 14464-46-1) Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effectsCauses damage to organs through prolonged or repeated exposure.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

CRISTOBALITE (CAS 14464-46-1)

Cancer lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

US state regulations

California Proposition 65



WARNING: This product can expose you to QUARTZ, which is known to the State of California to cause

cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

Material name: CORETEX™

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

CRISTOBALITE (CAS 14464-46-1) QUARTZ (CAS 14808-60-7)

International Inventories

Taiwan

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Taiwan Chemical Substance Inventory (TCSI)

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

23-February-2016 Issue date 21-January-2019 **Revision date**

Version #

United States & Puerto Rico

HMIS® ratings Health: 3*

Flammability: 0 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 0 Instability: 0

The information provided in this Safety Data Sheet is correct to the best of our knowledge, Disclaimer

information and belief at the date of its publication. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and completeness of such information for each particular use. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. CETCO, an MTI Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written

based on the best knowledge and experience currently available.

Composition / Information on Ingredients: Ingredients **Revision information**

Regulatory Information: United States

Material name: CORETEX™ SDS US

Yes

Yes