

SAFETY DATA SHEET

1. Identification

Product identifier	ENVIROSHEET	
Other means of identification	None.	
Recommended use	Not available.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/	Distributor information	
Manufacturer		
Company name	CETCO, an MTI Company	
Address	2870 Forbs Avenue	
	Hoffman Estates, IL 60192	
	United States	
Telephone	General Information	800 527-9948
Website	http://www.cetco.com/	
E-mail	safetydata@mineralstech.co	om
Emergency phone number	Emergency	1.866.519.4752/1 760 476 3962
Americas	1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962	

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Carcinogenicity	Category 1B
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	May cause cancer.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If exposed or concerned: Get medical advice/attention.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT	PETROLEUM ASPHALT	8052-42-4	60 - < 80
CALCIUM CARBONATE	LIMESTONE	1317-65-3	10 - < 30
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC [BASEOIL UNSPECIFIED] (CONC>=0.1%)		64742-52-5	10 - < 20
Other components below reportab	le levels		10 - < 20

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret

4. First-aid measures	
Inhalation	If exposed to excessive levels of dusts or fumes, remove to fresh air and get medical attention if cough or other symptoms develop.
Skin contact	Wash off with warm water and soap. Get medical attention if irritation develops or persists.
Eye contact	Immediately flush eyes with plenty of water for at least 20 minutes. Get medical attention if irritation develops or persists.
Ingestion	If swallowed, rinse mouth with water (only if the person is conscious). Ingestion may cause transient irritation of throat, stomach and gastrointestinal tract. Consult a physician if necessary. Give several glasses of water.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Foam. Dry powder. Dry chemical, CO2, water spray or regular foam. Carbon dioxide (CO2).
Unsuitable extinguishing media	Water. Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.

Firefighters should wear full protective clothing including self contained breathing apparatus.

and precautions for firefighters	
Fire fighting equipment/instructions	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific methods	Move containers from fire area if you can do so without risk.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Special protective equipment

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	This product is miscible in water. Stop the flow of material, if this is without risk. Sweep up or gather material and place in appropriate container for disposal. Containment of this material should not be necessary.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. No special environmental precautions required.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged or repeated skin contact with this material. Avoid prolonged

and understood. Avoid prolonged or repeated skin contact with this material. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat, sparks, and flame. Store in a cool, dry place out of direct sunlight. Keep containers tightly closed in a dry, cool and well-ventilated place.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
CALCIUM CARBONATE (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. OSHA Table Z-3 (29 CFI Additional components	Type	Value	Form
INERT OR NUISANCE DUSTS	TWA	5 mg/m3	Respirable fraction.
20010		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.
US. NIOSH: Pocket Guide to Components	o Chemical Hazards Type	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.
CALCIUM CARBONATE	TWA	5 mg/m3	Respirable.
(CAS 1317-65-3)		0g,0	
		10 mg/m3	Total
Biological limit values	No biological exposure limits noted for	or the ingredient(s).	
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
Individual protection measures, Eye/face protection	such as personal protective equipm Wear safety glasses with side shields		
Skin protection			
Hand protection	Wear protective gloves.		
Other	Wear appropriate chemical resistant clothing. When material is heated, wear gloves to protect against thermal burns.		
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. When dusts or thermal processing fumes are generated and ventilation is no sufficient to effectively remove them, appropriate NIOSH/MSHA approved respiratory protection must be provided.		
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Use good industrial hygiene practices in handling this material.		
9. Physical and chemical	properties		
Appearance	Fabric/Mat		
Physical state	Solid.		
Form	Solid. Roll.		
Color	Black.		
Odor	Petroleum		
Odor threshold	Not available.		
рН	Not available.		
Melting point/freezing point	190 - 230 °F (87.78 - 110 °C)		
Initial boiling point and boiling range	700 °F (371.11 °C) estimated		
Flash point	450.0 °F (232.2 °C) Cleveland Open	Сир	
Evaporation rate	Not available.		
	N		

Material name: ENVIROSHEET

Flammability (solid, gas)

4826 Version #: 09 Revision date: 04-May-2020 Issue date: 04-May-2020

Not available.

Upper/lower flammability or explosive limits

Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Negligible
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	905 °F (485 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	1.00 g/cm3 estimated
Flammability class	Combustible IIIB estimated
Percent volatile	Negligible
Pour point	>= 300 °F (>= 148.89 °C) >= 300 °F (>= 148.89 °C)
Specific gravity	1 - 1.2
VOC	Negligible CARB

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable at normal conditions.
Possibility of hazardous reactions	Will not occur.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Acids. Strong oxidizing agents. Fluorine.
Hazardous decomposition products	Upon decomposition this product emits acrid dense smoke with carbon dioxide, carbon monoxide, water and other products of combustion.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Not available.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Product	Species	Test Results	
ENVIROSHEET			
<u>Acute</u>			
Dermal			
LD50	Rabbit	2722 mg/kg	
Inhalation	_		
LC50	Rat	13.35 mg/l/4h	
Components	Species	Test Results	
DISTILLATES (PETROLEUM), H 64742-52-5)	YDROTREATED HEAVY NAPHTHEN	IC [BASEOIL UNSPECIFIED] (CONC>=0.1%) (CAS	
<u>Acute</u>			
Dermal			
LD50	Rabbit	2000 mg/kg	
Inhalation			
LC50	Rat	2.18 mg/l/4h	
Oral			
LD50	Rat	5000 mg/kg	
* Estimates for an dust many			
Skin corrosion/irritation	be based on additional component da		
	Prolonged skin contact may cause		
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.		
Respiratory or skin sensitizatio			
Respiratory sensitization	Not available.		
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure. This material contains petroleum asphalt. IARC has determined that there is inadequate evidence that undiluted, air-refined asphalt is carcinogenic to animals. There is only limited evidence that undiluted, steam-refined and cracking-residue asphalt are carcinogenic to animals. Additionally, IARC has concluded that there is inadequate evidence that asphalt asphalt are carcinogenic to animals.		
	cancer in animals. IARC has concl asphalt extracts in animals. Theref liquefied in hydrocarbon solvents) r or intermittent skin contact with this	act with some solvent extracts of asphalts have produced skin luded that there is sufficient evidence for the carcinogenicity of fore, "cutbacks" (asphalts that are diluted, dissolved, or may also be implicated as potentially carcinogenic. While brief stype of product is not expected to cause harm, those workers hygiene and who are exposed repeatedly via skin contact may	
	Condensed asphalt fumes, which are generated under laboratory conditions and are chemically different from those found during typical asphalt operations, have been reported to cause bacterial mutations. However, inhalation of asphalt fumes by laboratory animals, during controlled studies, did not produce lung cancer. Additionally, human studies have not established a link between lung cancer and asphalt fume exposure to date.		
	This product may contain trace amounts of polynuclear aromatic hydrocarbons (PAHs) as naturally occurring constituents of crude oils from which asphalt is derived. Some PAHs have been shown to be carcinogenic after prolonged or repeated skin contact in laboratory animals.		
IARC Monographs. Overall	Evaluation of Carcinogenicity		
ASPHALT (CAS 8052-4)		Possibly carcinogenic to humans. 053)	
Not listed.			
	ogram (NTP) Report on Carcinogen	s	
Not listed.			
Reproductive toxicity	This product is not expected to cau	se reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.		

Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not available.
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.
Further information	Information given is based on data on the components and the toxicology of similar products. No data is available on the product itself.

12. Ecological information

Ecotoxicity	No data available for this product.		
Components		Species	Test Results
DISTILLATES (PETROLEUN 64742-52-5)	I), HYDROTF	REATED HEAVY NAPHTHEN	NIC [BASEOIL UNSPECIFIED] (CONC>=0.1%) (CAS
Aquatic			
Crustacea	EC50	Daphnia	1000.0001 mg/L, 48 Hours
Fish	LC50	Fish	5000.0001 mg/L, 96 Hours
* Estimates for product may	be based on	additional component data n	ot shown.
Persistence and degradability	No data is	available on the degradabilit	y of this product.
Bioaccumulative potential	No data a	vailable.	
Mobility in soil	No data a	vailable.	
Other adverse effects			s (e.g. ozone depletion, photochemical ozone creation warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not available. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations

OSHA Process Safety Standard: This material is not known to be hazardous by the OSHA Highly Hazardous Process Safety Standard, 29 CFR 1910.119. This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4) ASPHALT (CAS 8052-42-4) Listed. SARA 304 Emergency release notification Not regulated. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) Not listed. Superfund Amendments and Reauthorization Act of 1986 (SARA) SARA 302 Extremely hazardous substance Not listed. SARA 311/312 Hazardous No (Exempt) chemical SARA 313 (TRI reporting) Not regulated. Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Not regulated. Safe Drinking Water Act Not regulated. (SDWA) **US state regulations** WARNING: This product contains a chemical known to the State of California to cause cancer. **California Proposition 65** WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Listed: January 1, 1990

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

ASPHALT (CAS 8052-42-4) DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC [BASEOIL UNSPECIFIED] (CONC>=0.1%) (CAS 64742-52-5)

International Inventories

ASPHALT (CAS 8052-42-4)

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	04-May-2020
Revision date	04-May-2020

Version #	09
Further information	This safety datasheet only contains information relating to safety and does not replace any product information or product specification.
HMIS® ratings	Health: 3* Flammability: 0 Physical hazard: 0
NFPA ratings	Health: 1 Flammability: 0 Instability: 0
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and completeness of such information for each particular use.
	Third party materials: Insofar as materials not manufactured or supplied by this manufacturer are used in conjunction with, or instead of this product, it is the responsibility of the customer to obtain, from the manufacturer or supplier, all technical data and other properties relating to these and other materials and to obtain all necessary information relating to them. No liability can be accepted in respect of the use of this product in conjunction with materials from another supplier. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.
Revision information	Product and Company Identification: Alternate Trade Names