

SAFETY DATA SHEET

1. Identification

Product identifier	LDC 60V	
Other means of identification	None.	
Recommended use	Not available.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Manufacturer		
Company name	CETCO, an MTI Company	
Address	2870 Forbs Avenue Hoffman Estates, IL 60192 United States	
Telephone	General Information	800 527-9948
Website	http://www.cetco.com/	
E-mail	safetydata@mineralstech.com	
Emergency phone number	Emergency	1.866.519.4752/1 760 476 3962
Americas	1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962	

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 4
Health hazards	Acute toxicity, inhalation	Category 4
	Sensitization, respiratory	Category 1
	Sensitization, skin	Category 1
	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 1A
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	Combustible liquid. May cause an allergic skin reaction. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause genetic defects. May cause cancer.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from flames and hot surfaces-No smoking. Avoid breathing dust. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.
Response	If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). If skin irritation or rash occurs: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison center/doctor. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information 24% of the mixture consists of component(s) of unknown acute oral toxicity. 34% of the mixture consists of component(s) of unknown acute dermal toxicity. 34% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 34% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Clarified oils, petroleum, catalytic cracked		64741-62-4	40 - < 70
CALCIUM CARBONATE	LIMESTONE	1317-65-3	10 - < 30
CALCIUM OXIDE (LIME)		1305-78-8	3 - < 7
CARBON BLACK		1333-86-4	3 - < 7
STODDARD SOLVENT		8052-41-3	1 - < 5
Hydrotreated heavy naphthenic distillate		64742-52-5	0.5 - < 1.5
Benzenesulfonyl isocyanate, 4-methyl-		4083-64-1	< 1
DIBUTYL TIN DILAURATE		77-58-7	< 1
Toluene-2,4-diisocyanate		584-84-9	< 1
Other components below reportable levels			5 - < 10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove to fresh air. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If the affected person is not breathing, apply artificial respiration. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a poison center or doctor/physician.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation develops or persists. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Ingestion	Call a physician or Poison Control Center immediately. If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting. Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation. Coughing. Difficulty in breathing. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Dry chemical, CO2, water spray or regular foam.
Unsuitable extinguishing media	Water. Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Not a fire hazard. Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of dust. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all sources of ignition or flammables that may come into contact with a spill of this material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Use clean non-sparking tools to collect absorbed material.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Sweep up or vacuum up spillage and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Do not flush into surface water or sanitary sewer system.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use this product with adequate ventilation. Minimize dust generation and accumulation. Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Use spark-proof tools and explosion-proof equipment. Ground and bond containers when transferring material. Do not get this material in contact with skin or eyes. Do not breathe gas/fumes/vapor/spray. Wash hands after handling and before eating.

Avoid breathing dust. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep in a dry, cool and well-ventilated place. Keep away from heat, sparks, and flame. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Keep container closed when not in use. Store in a well-ventilated place. Keep this material away from food, drink and animal feed. Keep out of the reach of children. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
TRADE SECRET (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
TRADE SECRET (CAS 1305-78-8)	PEL	5 mg/m3	
TRADE SECRET (CAS 1333-86-4)	PEL	3.5 mg/m3	

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
TRADE SECRET (CAS 8052-41-3)	PEL	2900 mg/m3	
		500 ppm	
Toluene-2,4-diisocyanate (CAS 584-84-9)	Ceiling	0.14 mg/m3	
		0.02 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
TRADE SECRET (CAS 1305-78-8)	TWA	2 mg/m3	
TRADE SECRET (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
TRADE SECRET (CAS 8052-41-3)	TWA	100 ppm	
Toluene-2,4-diisocyanate (CAS 584-84-9)	STEL	0.005 ppm	Inhalable fraction and vapor.
	TWA	0.001 ppm	Inhalable fraction and vapor.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
TRADE SECRET (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
TRADE SECRET (CAS 1305-78-8)	TWA	2 mg/m3	
TRADE SECRET (CAS 1333-86-4)	TWA	0.1 mg/m3	
TRADE SECRET (CAS 8052-41-3)	Ceiling	1800 mg/m3	
	TWA	350 mg/m3	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Toluene-2,4-diisocyanate (CAS 584-84-9)	5 µg/g	Toluene diamine (sum of 2,4- and 2,6-isomers), with hydrolysis	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US ACGIH Threshold Limit Values: Skin designation

Toluene-2,4-diisocyanate (CAS 584-84-9) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Eye/face protection

Applicable for industrial settings only. Wear safety glasses with side shields (or goggles). Wear safety glasses; chemical goggles (if splashing is possible). Eye wash fountain is recommended.

Skin protection

Hand protection

Applicable for industrial settings only. Wear appropriate chemical resistant gloves.

Other	Applicable for industrial settings only. Where contact is likely, wear chemical-resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield. Use of an impervious apron is recommended. Use of protective coveralls and long sleeves is recommended.
Respiratory protection	Applicable for industrial settings only. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection. Wear positive pressure self-contained breathing apparatus (SCBA). If ventilation is not sufficient to effectively prevent buildup of aerosols or vapors, appropriate NIOSH/MSHA respiratory protection must be provided. A NIOSH- approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. Use good industrial hygiene practices in handling this material.

9. Physical and chemical properties

Appearance	Liquid.
Physical state	Solid.
Form	Solid. liquid
Color	dark brown
Odor	Petroleum Solvent.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	4661.6 °F (2572 °C) estimated
Initial boiling point and boiling range	6377 °F (3525 °C) estimated
Flash point	180.0 °F (82.2 °C) Setflash
Evaporation rate	Slower than Ether
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.00001 hPa estimated
Vapor density	Vapors are heavier than air and may travel along the floor and in the bottom of containers
Relative density	1.2 g/cm ³
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	1.37 g/cm ³ estimated
Explosive properties	Not explosive.
Flammability class	Combustible IIIA estimated
Flash point class	Combustible IIIA
Oxidizing properties	Not oxidizing.

Percent volatile	7 %
Specific gravity	1.2
VOC	7.28 % VOC Method 310 87 g/l Regulatory VOC (less water and exempt solvent)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable at normal conditions.
Possibility of hazardous reactions	Will not occur.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Water. Acids. Strong oxidizing agents. Alcohols. Amines. Fluorine. Incompatible with strong acids and bases.
Hazardous decomposition products	At thermal decomposition temperatures, carbon monoxide and carbon dioxide.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact	May cause an allergic skin reaction.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Coughing. Difficulty in breathing. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Harmful if inhaled.

Product	Species	Test Results
LDC 60V		
Acute Inhalation		
LC50	Rat	926 mg/l/4h
Components	Species	Test Results
Benzenesulfonyl isocyanate, 4-methyl- (CAS 4083-64-1)		
Acute Inhalation		
LC50	Rat	640 mg/l/4h
CALCIUM OXIDE (LIME) (CAS 1305-78-8)		
Acute Oral		
LD50	Rat	500 mg/kg
CARBON BLACK (CAS 1333-86-4)		
Acute Oral		
LD50	Rat	> 8000 mg/kg
Clarified oils, petroleum, catalytic cracked (CAS 64741-62-4)		
Acute Dermal		
LD50	Rabbit	2000 mg/kg
	Rat	2000 mg/kg
Acute Oral		
LD50	Rat	4300 mg/kg

Components	Species	Test Results
Toluene-2,4-diisocyanate (CAS 584-84-9)		
Acute		
Inhalation		
LC50	Rat	14 mg/l/4h 14 mg/l, 4 Hours
Oral		
LD50	Rat	5800 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
ACGIH sensitization		
TOLUENE-2,4-DIISOCYANATE, INHALABLE FRACTION AND VAPOR (CAS 584-84-9)		Dermal sensitization Respiratory sensitization
Respiratory sensitization	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	May cause genetic defects.	
Carcinogenicity	May cause cancer.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
CARBON BLACK (CAS 1333-86-4)	2B Possibly carcinogenic to humans.	
STODDARD SOLVENT (CAS 8052-41-3)	3 Not classifiable as to carcinogenicity to humans.	
Toluene-2,4-diisocyanate (CAS 584-84-9)	2B Possibly carcinogenic to humans.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)		
Not regulated.		
US. National Toxicology Program (NTP) Report on Carcinogens		
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.	

12. Ecological information

Ecotoxicity No data available for this product.

Components	Species	Test Results
CALCIUM OXIDE (LIME) (CAS 1305-78-8)		
Aquatic		
Fish	LC50	Fish 1070 mg/L, 96 Hours
Clarified oils, petroleum, catalytic cracked (CAS 64741-62-4)		
Aquatic		
Fish	LC50	Fish 48 mg/L, 96 Hours
Toluene-2,4-diisocyanate (CAS 584-84-9)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 108.8 - 240.4 mg/l, 96 hours
Persistence and degradability	No data is available on the degradability of this product.	
Bioaccumulative potential		
Partition coefficient n-octanol / water (log Kow)		
DIBUTYL TIN DILAURATE	3.12	
STODDARD SOLVENT	3.16 - 7.15	

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel]
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT
Not regulated as dangerous goods.

IATA
Not regulated as dangerous goods.

IMDG
Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Toluene-2,4-diisocyanate (CAS 584-84-9) 0.1 % One-Time Export Notification only.

TSCA Chemical Action Plans, Chemicals of Concern

Toluene-2,4-diisocyanate (CAS 584-84-9) Toluene Diisocyanate (TDI) And Related Compounds Action Plan [RIN 2070-ZA14]

CERCLA Hazardous Substance List (40 CFR 302.4)

Toluene-2,4-diisocyanate (CAS 584-84-9) Listed.

SARA 304 Emergency release notification

Benzene, 2,4-diisocyanato-1-methyl- (CAS 584-84-9) 100 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
Toluene-2,4-diisocyanate	584-84-9	100	500		

SARA 311/312 Hazardous chemical No (Exempt)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Toluene-2,4-diisocyanate	584-84-9	< 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Toluene-2,4-diisocyanate (CAS 584-84-9)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Toluene-2,4-diisocyanate (CAS 584-84-9)

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

California Proposition 65



WARNING: This product can expose you to CARBON BLACK, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

CARBON BLACK (CAS 1333-86-4)

Listed: February 21, 2003

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Benzenesulfonyl isocyanate, 4-methyl- (CAS 4083-64-1)

CARBON BLACK (CAS 1333-86-4)

Clarified oils, petroleum, catalytic cracked (CAS 64741-62-4)

Hydrotreated heavy naphthenic distillate (CAS 64742-52-5)

STODDARD SOLVENT (CAS 8052-41-3)

Toluene-2,4-diisocyanate (CAS 584-84-9)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 18-August-2014

Revision date 14-February-2019

Version # 11

Further information This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

HMIS® ratings Health: 3*
Flammability: 2
Physical hazard: 0

NFPA ratings Health: 3
Flammability: 2
Instability: 0

Disclaimer

CETCO, an MTI Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and completeness of such information for each particular use.

Third party materials: Insofar as materials not manufactured or supplied by this manufacturer are used in conjunction with, or instead of this product, it is the responsibility of the customer to obtain, from the manufacturer or supplier, all technical data and other properties relating to these and other materials and to obtain all necessary information relating to them. No liability can be accepted in respect of the use of this product in conjunction with materials from another supplier. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

Composition / Information on Ingredients: Ingredients
Composition/information on ingredients: Composition comments
Physical & Chemical Properties: Multiple Properties
Physical and chemical properties: Form
Toxicological information: Reproductivity
Ecological information: Other adverse effects
Regulatory information: California Proposition 65
GHS: Qualifiers