

SAFETY DATA SHEET

1. Identification

Product identifier ULTRASEAL® AB

Other means of identification None

Recommended use Not available.

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

Category 1

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

CETCO, an MTI Company Company name **Address** 2870 Forbs Avenue

Hoffman Estates, IL 60192

United States

Telephone **General Information** 800 527-9948

Website http://www.cetco.com/

E-mail safetydata@mineralstech.com

Emergency 1.866.519.4752/1 760 476 3962 **Emergency phone number**

Americas 1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962

2. Hazard(s) identification

Not classified. Physical hazards

Health hazards Carcinogenicity Category 1A

Specific target organ toxicity, repeated

exposure

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Do not handle until all safety precautions have been read and understood. Do not breathe dust.

Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear

protective gloves/protective clothing/eye protection/face protection.

If exposed or concerned: Get medical advice/attention. Response Store in accordance with local/regional/national regulations. **Storage**

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ACRYLIC RESIN		9003-01-4	26

Material name: ULTRASEAL® AB SDS US

Chemical name	Common name and synonyms	CAS number	%
SODIUM ACRYLATE		7446-81-3	2
Other components below reportable levels			72
Constituents			

Chemical name	Common name and synonyms	CAS number	%
QUARTZ (SIO2)		14808-60-7	<= 4.3
CRISTOBALITE		14464-46-1	<= 1.4

^{#:} This substance has been assigned Community workplace exposure limit(s).

Composition comments

Bentonite contains naturally occurring crystalline silica (not listed in Annex I of Directive 67/548/EEC) in quantities less than 6%. Occupational Exposure Limits for constituents are listed in Section 8.

4. First-aid measures

Inhalation Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel.

Get medical attention, if needed.

Skin contact Get medical attention if irritation develops or persists. No special measures required.

Flush eyes immediately with large amounts of water. If irritation persists get medical attention. Eve contact If ingestion of a large amount does occur, seek medical attention. No special measures required. Ingestion

Most important Prolonged exposure may cause chronic effects.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Dry chemical, CO2, water spray or regular foam. Use any media suitable for the surrounding fires.

None known.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Material can be slippery when wet.

Fire fighting

equipment/instructions

Use water spray to cool unopened containers.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

Not a fire hazard. No unusual fire or explosion hazards noted. General fire hazards

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Material can be slippery when wet. Wear appropriate protective equipment and clothing during clean-up. Wear a dust mask if dust is generated above exposure limits. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection,

see section 8 of the SDS.

Methods and materials for containment and cleaning up Avoid the generation of dusts during clean-up. This product is miscible in water. Collect dust or particulates using a vacuum cleaner with a HEPA filter. Stop the flow of material, if this is without risk. Cover with plastic sheet to prevent spreading. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS. Reduce airborne dust and prevent scattering by moistening with water.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

SDS US

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. In case of insufficient ventilation, wear suitable respiratory equipment. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

No special restrictions on storage with other products. Store in original tightly closed container. Store in a dry place. Guard against dust accumulation of this material. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS). Keep in a cool, well-ventilated place.

8. Exposure controls/personal protection

Occupational exposure limits

Constituents	nissible Exposure Limits (PEL) for Air Co Type	Value	Form
CRISTOBALITE (CAS 14464-46-1)	PEL	0.05 mg/m3	Respirable dust.
QUARTZ (SIO2) (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 Pern Constituents	nissible Exposure Limits (PEL) for Minera Type	al Dusts (29 CFR 1910.1000) Value	Form
INERT OR NUISANCE DUSTS (CAS SEQ250)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Lir	* *		_
Constituents	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
	gerous to Life or Health (IDLH) Values, as		
Constituents	Туре	Value	
CRISTOBALITE (CAS 14464-46-1)	IDLH	25 mg/m3	
QUARTZ (SIO2) (CAS 14808-60-7)	IDLH	50 mg/m3	
	e to Chemical Hazards Recommended Ex		_
Constituents	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable dust.
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
ogical limit values	No biological exposure limits noted for	the ingredient(s).	
osure guidelines	Some of the components of this product of the physical pature of this product of		

Material name: ULTRASEAL® AB

SDS US

5331 Version #: 13 Revision date: 24-September-2024 Issue date: 02-March-2019

of the physical nature of this product, dust generation is not expected.

Appropriate engineering controls

If engineering measures are not sufficient to maintain concentrations of dust particulates below the OEL, suitable respiratory protection must be worn. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear dust goggles. Avoid contact with eyes. Eye wash fountain is recommended.

Skin protection

Hand protection Not normally needed. Wear appropriate chemical resistant gloves.

Other Use of an impervious apron is recommended. No special protective equipment required.

Exposure Limit.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Use good industrial hygiene practices in handling this material.

9. Physical and chemical properties

Appearance The product consists of bentonite granules between geotextile layers

Physical state Solid.
Form Solid.

ColorNot available.OdorNot available.Odor thresholdNot available.pH $\geq 7 - \leq 11$ $\geq 7 - \leq 11$

Melting point/freezing point 842 °F (450 °C) estimated

Initial boiling point and boiling

range

Not available.

Flash point Non-flammable
Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits
Explosive limit - lower (%) Non-explosive

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Negligible

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 1.54 g/cm3 estimated

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 1.54 estimated

VOC CARB

Material name: ULTRASEAL® AB
5331 Version #: 13 Revision date: 24-September-2024 Issue date: 02-March-2019

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Stable at normal conditions.

Possibility of hazardous

reactions

Will not occur.

Conditions to avoid None known. Contact with incompatible materials.

Incompatible materials None known.

Hazardous decomposition None known.

products

11. Toxicological information

Information on likely routes of exposure

InhalationNot available.Skin contactNot available.Eye contactNot available.IngestionNot available.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

ACRYLIC RESIN (CAS 9003-01-4)

Acute Dermal

LD50 Rat > 3 g/kg

Inhalation

LC50 Rat 1.71 mg/l, 4 Hours

Oral

LD50 Rat > 1000 mg/kg

2500 mg/kg

Skin corrosion/irritation Not available.

Serious eye damage/eye

irritation

Mild irritant to eyes (according to the modified Kay & Calandra criteria) Mild irritant to eyes

(according to the modified Kay & Calandra criteria)

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization According to the classification criteria of the European Union, the product is not considered as

being a skin irritant.

Germ cell mutagenicity Not available.

Carcinogenicity In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded

that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing

regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable

dust and respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

CRISTOBALITE (CAS 14464-46-1) 1 Carcinogenic to humans. QUARTZ (SIO2) (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

CRISTOBALITE (CAS 14464-46-1) Cancer QUARTZ (SIO2) (CAS 14808-60-7) Cancer

Material name: ULTRASEAL® AB

US. National Toxicology Program (NTP) Report on Carcinogens

CRISTOBALITE (CAS 14464-46-1) Known To Be Human Carcinogen. QUARTZ (SIO2) (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity

Specific target organ toxicity -

Not available.

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

Not available.

Chronic effects

single exposure

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)

In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)

According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Some of the components of this product are hazardous in the respirable form. However, because of the physical nature of this product, dust generation is not expected.

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

12. Ecological information

Ecotoxicity This material is not expected to be harmful to aquatic life.

Components Species Test Results

ACRYLIC RESIN (CAS 9003-01-4)

Aquatic

Fish LC50 Fish 580 mg/L, 96 Hours

No data is available on the degradability of this product.

Persistence and degradability

No data available.

Bioaccumulative potential Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations. Material

should be recycled if possible.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

Material name: ULTRASEAL® AB
5331 Version #: 13 Revision date: 24-September-2024 Issue date: 02-March-2019

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations OSHA Process Safety Standard: This material is not known to be hazardous by the OSHA Highly

Hazardous Process Safety Standard, 29 CFR 1910.119.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

CRISTOBALITE (CAS 14464-46-1) Cancer QUARTZ (SIO2) (CAS 14808-60-7) Cancer CRISTOBALITE (CAS 14464-46-1) lung effects QUARTZ (SIO2) (CAS 14808-60-7) lung effects

CRISTOBALITE (CAS 14464-46-1) immune system effects QUARTZ (SIO2) (CAS 14808-60-7) immune system effects

CRISTOBALITE (CAS 14464-46-1) kidney effects QUARTZ (SIO2) (CAS 14808-60-7) kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65



WARNING: This product can expose you to CRISTOBALITE: QUARTZ (SIO2), which is known to the State of

California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

CRISTOBALITE (CAS 14464-46-1) Listed: October 1, 1988 QUARTZ (SIO2) (CAS 14808-60-7) Listed: October 1, 1988

International Inventories

Country(s) or region Inventory name On inventory (yes/no)* Australia Australian Inventory of Industrial Chemicals (AICIS) Yes Canada Domestic Substances List (DSL) No Canada Non-Domestic Substances List (NDSL) Yes

Material name: ULTRASEAL® AB 5331 Version #: 13 Revision date: 24-September-2024 Issue date: 02-March-2019 Country(s) or region Inventory name On inventory (yes/no)* China Inventory of Existing Chemical Substances in China (IECSC) Nο

European Inventory of Existing Commercial Chemical Europe

Substances (EINECS)

Europe European List of Notified Chemical Substances (ELINCS) No Japan Inventory of Existing and New Chemical Substances (ENCS) Yes Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes **Philippines** Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information, including date of preparation or last revision

02-March-2019 Issue date 24-September-2024 **Revision date**

Version # 13

This safety datasheet only contains information relating to safety and does not replace any product **Further information**

information or product specification.

HMIS® ratings Health: 3*

Flammability: 0 Physical hazard: 0

Health: 2 NFPA ratings

> Flammability: 0 Instability: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge. information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and completeness of such information for each particular use.

Third party materials: Insofar as materials not manufactured or supplied by this manufacturer are used in conjunction with, or instead of this product, it is the responsibility of the customer to obtain, from the manufacturer or supplier, all technical data and other properties relating to these and other materials and to obtain all necessary information relating to them. No liability can be accepted in respect of the use of this product in conjunction with materials from another supplier. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. CETCO, an MTI Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Revision information

Product and Company Identification: Product and Company Identification

Hazard(s) identification: Hazard statement Hazard(s) identification: Prevention Hazard(s) identification: Response Hazard(s) identification: Storage

Hazard(s) identification: Supplemental information Handling and storage: Precautions for safe handling

Handling and storage: Conditions for safe storage, including any incompatibilities

GHS: Classification

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).