

RAP 350FR

FIRE RATED PROTECTION CAP

DESCRIPTION

RAP 350FR is heavy duty 160-mils (4.0 mm) thick, fire rated reinforced rubberized asphalt protection cap sheet with granulated top surface. RAP 350FR is reinforced with tough, non-woven synthetic fibers that provide fire resistance properties and membrane that withstands wrinkling, buckling and fish mouths.

APPLICATIONS

RAP 350FR is embedded into the top surface of STRATASEAL HR as the cap layer protecting the hotapplied rubberized asphalt membrane from damage by subsequent toppings and typical construction traffic. It can be used in the STRATASEAL HR Protected Membrane Roof Assembly, Plaza Deck Assembly, Split-Slab Construction Assembly, Asphalt Paving Deck Assembly, Greenroof Assembly, or Landscaped Assembly as the protection layer. The granulated surface is UV resistant thereby RAP 350FR can be left as an exposed material.

INSTALLATION

Install RAP 350FR into the top surface of STRATASEAL HR hot-applied rubberized asphalt while it is still warm and tacky. Embed the sheet into the membrane ensuring a good bond. The lap lines will face upward when unrolling. Overlap all seams and laps of the protection layer 3" (75mm) and seal with STRATASEAL HR hot-applied rubberized asphalt in the seams and laps.

Cut as required to fit around all penetration and drainage details. RAP 350FR will lay flush against all edges and not terminate into Flashing. It is designed only as a protection sheet and should not be used as a Flashing membrane. Reference standard detail drawings for appropriate termination details. RAP 350FR protection sheet is compatible with Flash TS and Flash TG torch-weld Flashings, as well as, Flash SA self-adhering Flashing. Upon completion of RAP 350FR, install subsequent toppings as required.

PRECAUTIONS

RAP 350FR is designed as a protection course for STRATASEAL HR hot-applied rubberized asphalt and is not designed for use in built-up roof systems. RAP 350FR can be left exposed to prolonged UV exposure but should not be used as a traffic surface.

PACKAGING

RAP 350FR roll size is 39.4" (1m) x 32'-10" (10m) - 107 sq ft per roll.

Typical roll weight: 106-lbs (48.1kg).

RAP 350FR is packaged 20 rolls per pallet.

| TECHNICAL DATA | | |
|------------------------|-------------|--------------------------------|
| PROPERTY | TEST METHOD | TYPICAL VALUE |
| Tensile Strength @ 0°F | ASTM D5147 | 135 lbsF/in MD; 95 lbsF/in XMD |
| Elongation @ 0°F | ASTM D5147 | 4% MD; 4% XMD |
| Dimensional Stability | ASTM D5147 | 0.20% MD; 0.20% XMD |
| Low Temp Flexibility | ASTM D5147 | - 10°F (-23°C) |

North America: 847.851.1800 | 800.527.9948 | www.CETCO.com

UPDATED: JUNE 2015

© 2015 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

