

REVO-FIX

PROFILED EXPANDED METAL MESH STRIP

DESCRIPTION

REVO-FIX is a profiled expanded metal mesh strip designed for mechanically fixing WATERSTOP-RX and WATERSTOP-XP to cast-in-place concrete surfaces. Revo-Fix can be used as an alternative method to CETSEAL for securing WATERSTOP-RX or WATERSTOP-XP.

APPLICATIONS

Primary applications are:

- Fixing WATERSTOP-RX and WATERSTOP-XP to cast-in-place concrete construction joint surfaces

INSTALLATION

After preparing concrete surface, uncoil WATERSTOP-RX or WATERSTOP-XP leaving the release paper intact, then apply the exposed WATERSTOP-RX or WATERSTOP-XP face against the concrete, pushing firmly against the release paper to force the WATERSTOP-RX or WATERSTOP-XP into concrete undulations. As work proceeds, remove release paper, and locate REVO-FIX sections over the WATERSTOP-RX or WATERSTOP-XP, lapping the ends by 25 mm maximum. Nail through laps with REVO-FIX Fixings supplied, and provide one additional fixing in between (i.e. fixings at 300 mm c/c).

On irregular surfaces, ensure that WATERSTOP-RX OR WATERSTOP-XP remains in direct contact with the substrate along the entire installation on irregular surfaces e.g. Old to new slab junctions. BENTOSEAL can be used to provide a 'bed' for WATERSTOP-RX, followed by application of REVO-FIX (which may require additional nailing to allow it to conform to the surface profile). SEAL-X XP can be used to provide a 'bed' for WATERSTOP-XP, followed by application of REVO-FIX (which may require additional nailing to allow it to conform to the surface profile).

End-to-end or end-to-side REVO-FIX junctions are created by simple butt joints. Ensure continuity is achieved through REVO-FIX by pressing ends firmly together. Start at junctions; do not stretch WATERSTOP-RX or WATERSTOP-XP to fit. Also, do not overlap WATERSTOP-RX or WATERSTOP-XP.

Ensure correct safety gloves are worn during the installation of REVO-FIX.

LIMITATIONS

REVO-FIX is not designed for securing WATERSTOP-RX or WATERSTOP-XP to steel surfaces or around pipe penetrations. Please consult WATERSTOP-RX or WATERSTOP-XP technical data sheets for further information. REVO-FIX is designed solely for securing WATERSTOP-RX or WATERSTOP-XP to concrete surfaces.

PACKAGING

REVO-FIX is available in two sizes:

REVO-FIX 101 (for securing WATERSTOP-RX101); 25 mm x 1.0 m (30 No 1.0 m strips plus REVO-FIX Fixings per box).

REVO-FIX 103 (for securing WATERSTOP-RX103 and WATERSTOP-XP); 15 mm x 1.0 m (48 No 1.0 m strips plus REVO-FIX Fixings per box).

North America: 847.851.1800 | 800.527.9948 | www.cetco.com

UPDATED: JUNE 2015

© 2015 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.



CETCO