

RGT-100 FITTINGS

GROUT TUBE FITTINGS

DESCRIPTION

RGT-100 Fittings are polypropylene multi-barb fittings for use with CETCO's RGT-100 Reinforced Grout Tubes. RGT-100 Fittings are available in four variations; 90° Male Elbow, Male Straight Adapter, In-Line Straight Connector, and Threaded Pipe Cap.

APPLICATIONS

RGT-100 Fittings are inserted into the open end of the RGT-100 Reinforced Grout Tube to create simple connections and terminations allowing for post concrete pour grouting if necessary.

INSTALLATION

Insert the barbed end of the RGT-100 Fitting into the open end of the RGT-100 Reinforced Grout Tube until fitting is secure. Using a metal hose clamp, place around the RGT-100 Reinforced Grout Tube where the barb is located, fastening clamp tight and securing RGT-100 Fitting.

PACKAGING

RGT-100 Fittings come in 25mm (1") Hose ID x 25mm (1") thread. 90° Male Elbow Fittings are packaged 25 pieces/box. Male Straight Adaptor and Straight Connectors are packaged 50 pieces/box. Threaded Pipe Caps are packaged 50 pieces/box.



Straight Connector



90 Male Elbow



Male Straight Connector

PHYSICAL PROPERTIES

PROPERTY	TYPICAL VALUE
Working Pressure	150 PSI
Temperature Range	12°C (10°F) to 104°C (220°F)
Dimensions (Hose ID x Thread)	25mm (1") x 25mm (1") NPT

North America: 847.851.1800 | 800.527.9948 | www.CETCO.com

UPDATED: JUNE 2015

© 2015 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

