

VSA-300 FLASHING

SELF-ADHERING FLASHING

PRODUCT DESCRIPTION

VSA-300 FLASHING is a wide flashing membrane consisting of a heavy-duty seven layer polyethylene and EVOH barrier geomembrane coated on one side with a pressure sensitive adhesive. The highly aggressive pressure sensitive adhesive is designed to adhere to VINTEGRA and other CETCO waterproofing membranes and accessories.

APPLICATIONS

VSA-300 FLASHING is primarily used to seal the membrane roll end overlaps and field cut seams of VINTEGRA GB20. It can also be used at penetrations and transition tie-ins for under slab and property line applications.

INSTALLATION

Install VSA-300 FLASHING with the heavy-duty geomembrane side facing the prepared substrate. Position the adjacent VINTEGRA GB20 roll edges over the VSA-300 FLASHING to provide a minimum 100mm (4") overlaps.

Wipe clean VINTEGRA GB20 membrane surfaces to receive VSA-300 FLASHING to remove any dirt, dust or moisture. Then remove the release liner from the top surface of the VSA-300 FLASHING and place the adjacent VINTEGRA GB20 membrane edge over the flashing with a minimum 100mm (4") overlap. Using a silicone hand roller, firmly press the membrane to the flashing to achieve maximum adhesion.

It is recommended that concrete be poured within 60 days (45 days in hot climates) following the installation of VINTEGRA waterproofing systems. Following ACI guidelines, concrete must be placed carefully and consolidated properly to avoid damage to the membrane. Never use a sharp object to consolidate the concrete. Provide temporary protection from concrete overspray/splatter in areas where the flashing is adjacent to a concrete pour.

LIMITATIONS

- Surfaces must be clean and dry
- Install at temperatures of 4°C (25°F) or above
- Do not leave exposed for more than 60 days
- Designed for in-service temperatures below 54°C (130°F)

SAFETY

Workers should wear protective clothing and eye protection. Do not ingest. Refer to SDS for other warnings and product safety information.

PACKAGING

300mm x 15m (12" X 50-FT) Roll
2 Rolls per Box

North America: 847.851.1800 | 800.527.9948 | www.cetco.com

UPDATED: APRIL 2023

© 2023 Minerals Technologies Inc. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.cetco.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.



CETCO®