

HDD MIXING CHART

COARSE SOILS - RECYCLE				
PER 100 GALLONS FRESHWATER				
DRILLING CONDITIONS	MIXING ORDER	RECOMMENDED CETCO PRODUCTS	DOSAGE PER 100 GALS FRESHWATER	VISCOSITY SECONDS PER/QT
SAND	1	SODA ASH	0.25-0.5 LBS	50-60
	2	HYDRAUL-EZ (NEW) OR SUPER GEL-X	25-30 LBS	
	3	REL-PAC XTRA-LOW OR SUPER PAC XTRA-LOW	0.5 LBS 0.5-1 QT	
	4	SUSPEND-IT	0.5 LB	
	5	IF CLAY PRESENT DRILL-TERGE AND INSTA-VIS LOW VISCOSITY	0.5-0.75 QT 0.25-1.0 LB	
SAND & GRAVEL	1	SODA ASH	0.25-0.5 LBS	50-65
	2	HYDRAUL-EZ (NEW) OR SUPER GEL-X	25-30 LBS	
	3	REL-PAC XTRA-LOW OR SUPER PAC XTRA-LOW	0.5-1.0 LB 0.5-1 QT	
	4	SUSPEND-IT	0.5 LB	
	5	IF CLAY PRESENT DRILL-TERGE AND INSTA-VIS LOW VISCOSITY	0.5-0.75 QT 0.25-1.0 LB	
GRAVEL & COBBLE	1	SODA ASH	0.25-0.5 LBS	60-75
	2	HYDRAUL-EZ (NEW) OR SUPER GEL-X	30-35 LBS	
	3	REL-PAC XTRA-LOW OR SUPER PAC XTRA-LOW	1-1.5 LBS 1-1.5 QTS	
	4	SUSPEND-IT	1 LB	

REACTIVE CLAYS OR UNKNOWN - RECYCLE				
DRILLING CONDITIONS	MIXING ORDER	RECOMMENDED CETCO PRODUCTS	DOSAGE PER 100 GALS FRESHWATER	VISCOSITY SECONDS PER QUART
CLAY	1	SODA ASH	0.25-0.5 LBS	35-45
	2	HYDRAUL-EZ (NEW) OR SUPER GEL-X	7-10 LBS	
	3	INSTA-VIS LOW VISCOSITY	0.25-1.0 LB	
	4	DRILL-TERGE	0.5-0.75 QT	
STICKY CLAY	1	SODA ASH	0.25-0.5 LBS	35-45
	2	HYDRAUL-EZ (NEW) OR SUPER GEL-X	7-10 LBS	
	3	INSTA-VIS LOW VISCOSITY	0.25-1.0 LB	

CETCO X-TORQUE - ROTATIONAL TORQUE REDUCER

TYPICAL APPLICATION - PER 100 GALLONS

DRILLING CONDITIONS	MIXING ORDER	RECOMMENDED CETCO PRODUCTS	DOSAGE PER 100 GALS FRESHWATER
ANY	ANY	CETCO X-TORQUE	1-2 QTS

HERCUL-EZ - EXTREME SOLIDS SUSPENSION MIXING RATIOS*

TYPICAL APPLICATION - PER 1000 GALLONS

	NUMBER OF BAGS (50 LB)	SODA ASH (LB)	HERCUL-EZ NUMBER OF BAGS (25 LB)
SUPER GEL-X	5	12	1.5
HYDRAUL-EZ (NEW)	5	12	1.5-2

NOTE: *HERCUL-EZ EXTREME SOLIDS SUSPENSION CAN BE USED FOR ANY UNCONSOLIDATED GROUND AND IS RECOMMENDED FOR COARSE SAND, GRAVEL, AND COBBLE.

North America: 847.851.1800 | 800.527.9948 | www.CETCO.com

UPDATED: JANUARY 2022

© 2022 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

