

BMR™ BENTONITE MUD REMOVER



Certified to
NSF/ANSI 60

DESCRIPTION

BMR is a non-phosphate granular product. BMR is certified to NSF/ANSI Standard 60, Drinking Water Treatment Chemicals - Health Effects.

RECOMMENDED USE

BMR removes bentonite that has been introduced as a drilling fluid and results in a tough layer of mud sometimes difficult to remove. Additionally, BMR removes naturally occurring clays that intrude into the gravel pack.

CHARACTERISTICS

- Highly concentrated for maximum yield
- Contains no phosphates
- Decreases development time and cost
- Has the ability to separate and disperse clay particles
- Increases well productivity

DIRECTIONS FOR USE

1. Calculate quantity of BMR required according to the dosage table. Normal dosage is 0.33 lb per gallon of water. If gravel pack is present, the volume of water in it should be accounted for as part of the total well volume. Typical porosity of gravel pack is 30-40%
2. Mix one part BMR to four parts water prior to pouring down casing. This helps the BMR dissolve thoroughly. Agitate the well lightly, and add water to force the BMR deeper into the gravel pack and formation.
3. Agitate the well as often as possible for a minimum of 12 hours. Well size and severity of blockage may increase or decrease agitation time. Agitate by surging, bailing, pumping, or jetting.
4. Pump the well a minimum of nine (9) full well volumes to effectively remove residual chemical and suspended clay particles.
5. (Optional) Chlorinate the well with a shock treatment of sodium hypochlorite to 500-1,000 ppm. Pump the well until free of chlorine.

PACKAGING

~50 lb (22.7 kg) pails, 32 per pallet. All pallets are plastic-wrapped. Keep container closed to prevent caking.



BMR DOSAGE TABLE (0.33 lb per gallon)

Well Diameter	Lbs/10 ft of Water
2"	0.54 lb
4"	2.16 lbs
6"	4.87 lbs
8"	8.66 lbs
10"	13.53 lbs
12"	19.48 lbs
14"	26.51 lbs
16"	34.63 lbs
18"	43.83 lbs
20"	54.11 lbs

North America: 847.851.1800 | 800.527.9948 | www.CETCO.com

UPDATED: MAY 2019

© 2019 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.



CETCO