

C/S GRANULAR™

30-50 MESH GRANULAR BENTONITE



Certified to NSF/ANSI/CAN 60

CETCO® CRUMBLES # 8

8-20 MESH GRANULAR BENTONITE

DESCRIPTION

C/S GRANULAR and CETCO CRUMBLES are granular bentonite products composed of polymer-free, dried bentonite in various mesh sizes. CETCO CRUMBLES are coarser in size than C/S GRANULAR. C/S GRANULAR and CETCO CRUMBLES are certified to NSF/ANSI/CAN Standard 60, Drinking Water Treatment Chemicals - Health Effects.

RECOMMENDED USE

May be used as casing seal, hole abandonment material, and for sealing earthen structures.

CHARACTERISTICS

- Less than 10% moisture
- Provide a positive seal
- Re-hydrates
- Will not shrink or crack



MIXING AND APPLICATION

Grouting Material	One bag CETCO CRUMBLES to 24 gallons (91 liters) water or 24 gallons water and 8 ounces (0.25 liters) ACCU-VIS
Dry Shallow Abandonment	Pour required amount directly down borehole; hydrate with freshwater
Earthen Structure Seal	Normal treatment is 3-5 pounds per ft ² (48-80 kg per m ²) depending on soil type

BULK DENSITY

65 lbs/ft³ (1.04 kg/L)

PACKAGING

~50 lb (~22.7 kg) bag, 48 per pallet. All pallets are plastic-wrapped.



North America: 847.851.1800 | 800.527.9948 | www.CETCO.com

UPDATED: OCTOBER 2021

© 2021 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

