

# DE-CHLOR™

## DECHLORINATION ADDITIVE

### DESCRIPTION

DE-CHLOR is a white granular crystal that neutralizes chlorine in municipal water. Chlorine in water supplies can destroy polymer drilling fluids.

### RECOMMENDED USE

Pre-treat make-up water with DE-CHLOR prior to mixing polymer drilling fluids to prevent premature breakdown, as well as to extend the yield and recycle life of polymer slurries.

### ADVANTAGES

- Boosts performance up to 50% without adding primary polymer
- Economical method for neutralizing chlorine
- Increases slurry life
- Stops chlorine from destroying polymer slurries

### CHARACTERISTICS

Appearance	White/off-white granular
Specific Gravity	1.69 lbs/liter
Solubility	50 grams/100 grams cold water

### MIXING AND APPLICATION

Add 0.5 lb DE-CHLOR per 1,000 gallons (0.25 kg DE-CHLOR per 3.8 m<sup>3</sup>) make-up water either through a VENTURI HOPPER or by sprinkling into the flow of water filling the borehole. Mix DE-CHLOR at the same time SODA ASH is added to the make-up water.

### PACKAGING

~50 lb (22.7 kg) pails, 32 per pallet. All pallets are plastic-wrapped.



North America: 847.851.1800 | 800.527.9948 | [www.CETCO.com](http://www.CETCO.com)

UPDATED: MAY 2019

© 2019 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit [www.CETCO.com](http://www.CETCO.com). CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

FORM: TDS\_DE-CHLOR\_AM\_EN\_201905



**CETCO**®