

# DRILL-TERGE™

## DRILLING DETERGENT/WETTING AGENT

### DESCRIPTION

DRILL-TERGE is a liquid solution of nonionic surfactants formulated to increase detergency and wetting properties of drilling fluids.

### RECOMMENDED USE

Designed to control interfacial tension and inhibit the hydration and dispersion of clay and shale.

### CHARACTERISTICS

- Assists in keeping the drill bit clean and prevents bit balling
- Designed to work in fresh or saltwater
- Mixes very easily
- Promotes settling of clays at the reserve pit/tank
- Reduces torque and drag associated with drilling in swelling clays

### MIXING AND APPLICATION

Add 2-3 quarts (6-9 liters) of DRILL-TERGE per 100 gallons (per 1.1 m<sup>3</sup>) of existing bentonite drilling fluid.

### PACKAGING

~45 lb (20.25 kg) pail, 48 per pallet, or ~495 lb (224.5 kg) drum, 4 per pallet. All pallets are plastic-wrapped.



North America: 847.851.1800 | 800.527.9948 | [www.CETCO.com](http://www.CETCO.com)

UPDATED: MAY 2019

© 2019 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit [www.CETCO.com](http://www.CETCO.com). CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.



**CETCO**®