

REL-PAC®

NATURAL CELLULOSIC POLYMER

DESCRIPTION

REL-PAC is a non-fermenting granular polymer designed for building a low solids drilling fluid with increased borehole stability. REL-PAC is a highly dispersible polymer, which prevents the formation of hard lumps or fish eyes, for maximum product efficiency.

RECOMMENDED USE

REL-PAC is designed to increase borehole stability in a variety of rotary and horizontal drilling applications.

CHARACTERISTICS

- Controls filtration rate and assists in forming thinner, less permeable filter cake
- Encapsulates solids for a total lower solids system
- Highly dispersible
- Improves fluid viscosity for effective removal of drill cuttings
- May be used in fresh or saltwater conditions
- Stabilizes drilled formations

MIXING AND APPLICATION

Mix at low shear through a mud hopper to avoid lumping and to minimize waste. Add 0.5 to 1.5 pounds (0.25 to 1 kg) of REL-PAC per 100 gallons (380 liters) of existing bentonite drilling fluid for hole stabilization. Dosage scoop included is equivalent to 1/2 lb.

PACKAGING

25 lb pail (11.3 kg) with dosage scoop, 36 per pallet or 50 lb bag (22.7 kg) 40 per pallet. All pallets are plastic-wrapped.

North America: 847.851.1800 | 800.527.9948 | www.CETCO.com

UPDATED: MAY 2019

© 2019 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

FORM: TDS_REL-PAC_AM_EN_201905



CETCO®