

# SUSPEND-IT™

## SUSPENSION ENHANCER

### DESCRIPTION

SUSPEND-IT is an easy mixing biopolymer additive used to control drilling fluid rheology.

### RECOMMENDED USE

Designed to enhance gel strength of the drilling fluid for improved suspension and transporting of drill cuttings, gravel, and cobble on long bores. SUSPEND-IT will perform effectively in fresh or saltwater.

### CHARACTERISTICS

- Easily dispersed in drilling fluids
- Enhances gel strength with little increase of viscosity
- Performs well in fresh and saltwater
- Transports larger cuttings, gravel and cobble easily on long bores
- Improves PV/YP
- Strengthens filter cake and improves bore stability

### MIXING AND APPLICATION

Pour slowly through a hopper at maximum shear to avoid lumping and to minimize waste. Add 0.5 to 1 pound per 100 gallons (0.25 to 0.5 kg per 380 liters) of SUSPEND-IT to existing drilling fluid. Dosage scoop included is equivalent to 1/2 lb.

### PACKAGING

35 lb (11.3 kg) pail, 36 per pallet. All pallets are plastic-wrapped.



North America: 847.851.1800 | 800.527.9948 | [www.CETCO.com](http://www.CETCO.com)

UPDATED: MAY 2019

© 2019 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit [www.CETCO.com](http://www.CETCO.com). CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

FORM: TDS\_SUSPEND-IT\_AM\_EN\_201905



**CETCO®**