SAFETY DATA SHEET



1. Identification

Product identifier RESISTEX® 100 CLT

Other means of identification None.

Recommended use Not available.

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name CETCO, a Minerals Technologies Company

Address 2870 Forbs Avenue

Hoffman Estates, IL 60192

United States

Telephone General Information 800.527.9948

Website http://www.cetco.com

E-mail safetydata@mineralstech.com

Emergency phone number 1.866.519.4752 (US, CA, 1 760.476.3962

MX)

Americas 1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1A

Specific target organ toxicity, repeated Category 1

exposure

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective

gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information 7.92% of the mixture consists of component(s) of unknown acute oral toxicity. 7.92% of the

mixture consists of component(s) of unknown acute dermal toxicity. 7.92% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 7.92% of the mixture

consists of component(s) of unknown long-term hazards to the aquatic environment.

Material name: RESISTEX® 100 CLT

14880 Version #: 09 Revision date: 24-February-2020 Issue date: 09-July-2018

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
QUARTZ (SIO2)		14808-60-7	5 - < 10
CRISTOBALITE		14464-46-1	1 - < 3
Hexanedioic acid		124-04-9	< 0.1
2-Propenamide		79-06-1	0.0002
Other components below re	portable levels		90 - 100

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and

delayed

Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

General information IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s)

involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Fire fighting

Specific methods

equipment/instructions

Move containers from fire area if you can do so without risk.

General fire hazards No unusual fire or explosion hazards noted.

Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Use standard firefighting procedures and consider the hazards of other involved materials.

Methods and materials for containment and cleaning up Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

14880 Version #: 09 Revision date: 24-February-2020 Issue date: 09-July-2018

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	Form
2-Propenamide (CAS 79-06-1)	PEL	0.3 mg/m3	
CRISTOBALITE (CAS 14464-46-1)	PEL	0.05 mg/m3	Respirable dust.
QUARTZ (SIO2) (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 (29 C Components	FR 1910.1000) Type	Value	Form
CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable.
14404-40-1)		1.2 mppcf	Respirable.
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
,		2.4 mppcf	Respirable.
Additional components	Туре	Value	Form
INERT OR NUISANCE DUSTS	TWA	5 mg/m3	Respirable fraction.
20010		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Lim Components	it Values Type	Value	Form
2-Propenamide (CAS 79-06-1)	TWA	0.03 mg/m3	Inhalable fraction and vapor.
CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
Hexanedioic acid (CAS 124-04-9)	TWA	5 mg/m3	
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide	to Chemical Hazards		
Components	Туре	Value	Form
2-Propenamide (CAS 79-06-1)	TWA	0.03 mg/m3	
CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable dust.
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
ogical limit values	No biological exposure limit	s noted for the ingredient(s).	
osure guidelines	Occupational exposure to n should be monitored and co	uisance dust (total and respirable) and rontrolled.	espirable crystalline silica
US - California OELs: Skir	n designation		
2-Propenamide (CAS 7 US - Minnesota Haz Subs:	•	Can be absorbed through the skin.	
2-Propenamide (CAS 7	(9-06-1)	Skin designation applies.	
US - Tennessee OELs: Ski	_		
2-Propenamide (CAS 7 US ACGIH Threshold Limi	′9-06-1) t Values: Skin designation	Can be absorbed through the skin.	
2-Propenamide (CAS 7	'9-06-1)	Can be absorbed through the skin.	

Material name: RESISTEX® 100 CLT

SDS US

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-Propenamide (CAS 79-06-1)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Propenamide (CAS 79-06-1)

Appropriate engineering

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Applicable for industrial settings only.

Skin protection

controls

Hand protection Wear appropriate chemical resistant gloves. Applicable for industrial settings only. Use of an impervious apron is recommended. Applicable for industrial settings only. Other

Respiratory protection Use a particulate filter respirator for particulate concentrations exceeding the Occupational

Exposure Limit. Applicable for industrial settings only.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Can be absorbed through the skin.

exposure limits have not been established, maintain airborne levels to an acceptable level.

9. Physical and chemical properties

The product consists of bentonite granules between geotextile layers Appearance

Solid. Physical state Solid, Mat **Form** Various. Color Odor Not available. Not available. Odor threshold Hq Not available. Melting point/freezing point Not available.

Initial boiling point and boiling

range

Not available.

Not available. Flash point **Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

0.00001 hPa estimated Vapor pressure

Not available. Vapor density Not available. Relative density

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature Not available. Not available. **Decomposition temperature** Not available. **Viscosity**

Other information

Density 0.76 g/cm3 estimated

Material name: RESISTEX® 100 CLT

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 0.76 estimated

VOC CARB

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

Conditions to avoid

reactions

No dangerous reaction known under conditions of normal use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with incompatible materials.

Incompatible materials Powerful oxidizers. Chlorine.

Hazardous decomposition

products

Toxic gas.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

CRISTOBALITE (CAS 14464-46-1)

<u>Acute</u>

Oral

LD50 Rat > 22500 mg/kg

Hexanedioic acid (CAS 124-04-9)

Acute Oral

LD50 Rat > 11000 mg/kg

Skin corrosion/irritationProlonged skin contact may cause temporary irritation. **Serious eye damage/eye**Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Material name: RESISTEX® 100 CLT

Carcinogenicity

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

2-Propenamide (CAS 79-06-1) 2A Probably carcinogenic to humans.

CRISTOBALITE (CAS 14464-46-1) 1 Carcinogenic to humans. QUARTZ (SIO2) (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

CRISTOBALITE (CAS 14464-46-1) Cancer QUARTZ (SIO2) (CAS 14808-60-7) Cancer US. National Toxicology Program (NTP) Report on Carcinogens

2-Propenamide (CAS 79-06-1) Reasonably Anticipated to be a Human Carcinogen.

CRISTOBALITE (CAS 14464-46-1) Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

QUARTZ (SIO2) (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - N

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be

harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

2-Propenamide (CAS 79-06-1)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 77 - 160 mg/l, 96 hours

Hexanedioic acid (CAS 124-04-9)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 97 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-Propenamide -0.67 Hexanedioic acid 0.08

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Material name: RESISTEX® 100 CLT

14880 Version #: 09 Revision date: 24-February-2020 Issue date: 09-July-2018

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

the IBC Code

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-Propenamide (CAS 79-06-1) Listed. Hexanedioic acid (CAS 124-04-9) Listed.

SARA 304 Emergency release notification

ACRYLAMIDE (CAS 79-06-1) 5000 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

CRISTOBALITE (CAS 14464-46-1)

QUARTZ (SIO2) (CAS 14808-60-7)

CRISTOBALITE (CAS 14464-46-1)

QUARTZ (SIO2) (CAS 14808-60-7)

Lung effects

QUARTZ (SIO2) (CAS 14808-60-7)

CRISTOBALITE (CAS 14464-46-1) immune system effects QUARTZ (SIO2) (CAS 14808-60-7) immune system effects

CRISTOBALITE (CAS 14464-46-1) kidney effects QUARTZ (SIO2) (CAS 14808-60-7) kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)	
2-Propenamide	79-06-1	5000		1000	10000	

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

2-Propenamide (CAS 79-06-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

Material name: RESISTEX® 100 CLT

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including 2-Propenamide, which is known to the State of

California to cause cancer and birth defects or other reproductive harm. For more information go

to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

2-Propenamide (CAS 79-06-1) Listed: January 1, 1990 QUARTZ (SIO2) (CAS 14808-60-7) Listed: October 1, 1988

California Proposition 65 - CRT: Listed date/Developmental toxin

2-Propenamide (CAS 79-06-1) Listed: February 25, 2011

California Proposition 65 - CRT: Listed date/Male reproductive toxin

2-Propenamide (CAS 79-06-1) Listed: February 25, 2011

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2-Propenamide (CAS 79-06-1) CRISTOBALITE (CAS 14464-46-1) QUARTZ (SIO2) (CAS 14808-60-7)

International Inventories

Country(s) or region	ountry(s) or region Inventory name		
Australia	Australian Inventory of Chemical Substances (AICS)	No	
Canada	Domestic Substances List (DSL)	No	
Canada	Non-Domestic Substances List (NDSL)	No	
China	Inventory of Existing Chemical Substances in China (IECSC)	No	
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No	
Europe	European List of Notified Chemical Substances (ELINCS)	No	
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No	
Korea	Existing Chemicals List (ECL)	No	
New Zealand	New Zealand Inventory	No	
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No	
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No	

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

09-July-2018 Issue date **Revision date** 24-February-2020

Version # 09

United States & Puerto Rico

Health: 3* HMIS® ratings

Flammability: 0 Physical hazard: 0

Health: 2 NFPA ratings

Flammability: 0 Instability: 0

SDS US

No

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and completeness of such information for each particular use.

The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. CETCO, a Minerals Technologies Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Revision information

Product and Company Identification: Alternate Trade Names

SDS US