SAFETY DATA SHEET



1. Identification

Product identifier VOLCLAY® BENTONITE

Other means of identification

CAS number 1302-78-9

Recommended useBentonite has a variety of uses. It can be used as a rheology modifier, binding agent, adsorbent,

hydraulic-barrier, and filler.

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name CETCO, an MTI Company

Address 2870 Forbs Avenue

Hoffman Estates, IL 60192

United States

Telephone General Information 800 527-9948

Website http://www.cetco.com/LT/
E-mail safetydata@mineralstech.com

Emergency phone number 1.866.519.4752 (US, CA, 1 760 476 3962

MX)

Americas 1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1A

Specific target organ toxicity, repeated Category 1

exposure

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective

gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

Material can be slippery when wet

Supplemental information 90% of the mixture consists of component(s) of unknown acute oral toxicity. 8% of the mixture

consists of component(s) of unknown acute dermal toxicity. 8% of the mixture consists of

component(s) of unknown acute hazards to the aquatic environment.

Material name: VOLCLAY® BENTONITE
4959 Version #: 24 Revision date: 25-October-2018 Issue date: 19-July-2018

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
QUARTZ (SIO2)		14808-60-7	6
CRISTOBALITE		14464-46-1	2
Other components below r	eportable levels		92

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Composition comments Occupational Exposure Limits for constituents are listed in Section 8.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

delayed

Prolonged exposure may cause chronic effects. symptoms/effects, acute and

Indication of immediate medical attention and special

treatment needed **General information** Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Use any media suitable for the surrounding fires.

Not applicable, non-combustible.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Firefighters should wear full protective gear. Use water spray to cool unopened containers.

Fire fighting

equipment/instructions

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

This material will not burn. Material can be slippery when wet No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Wear a dust mask if dust is generated above exposure limits. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

Material name: VOLCLAY® BENTONITE

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	PEL	0.05 mg/m3	Respirable dust.
QUARTZ (SIO2) (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 (29 C	FR 1910.1000)		
Components	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Constituents	Туре	Value	Form
INERT OR NUISANCE DUSTS	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Lim	it Values		
Components	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide	to Chemical Hazards		
Components	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable dust.
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
ogical limit values	No biological exposure limits noted for the	he ingredient(s).	
osure guidelines	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.		
ropriate engineering trols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. It exposure limits have not been established, maintain airborne levels to an acceptable level.		
		•	
vidual protection measure Eye/face protection	s, such as personal protective equipment Wear safety glasses with side shields (o		dustrial settings only.
Eye/face protection Skin protection		or goggles). Applicable for inc	
Eye/face protection	Wear safety glasses with side shields (o Suitable gloves can be recommended by Applicable for industrial settings only. Us	or goggles). Applicable for ind y the glove supplier. Applica	ble for industrial settings o
Eye/face protection Skin protection Hand protection	Wear safety glasses with side shields (o	or goggles). Applicable for inc y the glove supplier. Applica se of protective coveralls and iculate concentrations excee	ble for industrial settings o d long sleeves is ding the Occupational

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Lump, granular or fine powder.

Physical state Solid.

Form Solid. Various.
Color Various.
Odor None.

Odor threshold Not applicable.

pH 8.5 - 11

Melting point/freezing point $> 842 \, ^{\circ}\text{F} \, (> 450 \, ^{\circ}\text{C}) \, / \, \text{Not applicable}.$

Initial boiling point and boiling

range

Not applicable.

Flash point Not applicable.

Evaporation rate Not applicable.

Flammability (solid, gas) This product is not flammable.

Upper/lower flammability or explosive limits

Flammability limit - lower

riammability ilmit - lower

Not applicable.

(%)

Flammability limit - lower

Not applicable.

(%) temperature

Flammability limit - upper

(%)

Not applicable.

Flammability limit - upper

(%) temperature

Not applicable.

Explosive limit - lower (%) Not applicable.

Explosive limit - lower (%) Not applicable.

temperature

Explosive limit - upper (%) Not applicable.

Explosive limit - upper (%)

temperature

Not applicable.

Vapor pressureNot applicable.Vapor densityNot applicable.Relative density2.6 g/cm³

Solubility(ies)

Solubility (water) < 0.9 mg/l

Partition coefficient Not applicable.

(n-octanol/water)

Auto-ignition temperature

Not applicable.

> 932 °F (> 500 °C)

Viscosity

Not applicable.

Not applicable.

Viscosity temperature Not applicable.

Other information

Bulk density 0.9 - 1.4 g/cm³ **Explosive limit** Not applicable.

Explosive properties Not explosive. Not explosive

Explosivity
Not applicable.
Fire point
Not applicable.
Flame extension
Not applicable.
Flame projection
Not applicable.
Flammability
Not applicable.

Flammability (flash back) Flammability (Heat of

combustion)

Not applicable. Not applicable.

Flammability (Train fire) Not applicable. Flammability class Not applicable. Flash point class Not flammable **UVCB** Substance Molecular formula Not applicable. Molecular weight Oxidizing properties Not oxidizing. None.

0 % Percent volatile pH in aqueous solution 8.5 - 11

Specific gravity Not applicable.

VOC 0 % **CARB**

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the decomposition temperature. Contact with incompatible materials.

Incompatible materials Powerful oxidizers. Chlorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not known.

Components **Species Test Results**

CRISTOBALITE (CAS 14464-46-1)

Acute Oral

LD50 Rat > 22500 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Material name: VOLCLAY® BENTONITE

SDS US

Carcinogenicity

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

CRISTOBALITE (CAS 14464-46-1) 1 Carcinogenic to humans. QUARTZ (SIO2) (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

CRISTOBALITE (CAS 14464-46-1) Cancer QUARTZ (SIO2) (CAS 14808-60-7) Cancer US. National Toxicology Program (NTP) Report on Carcinogens

CRISTOBALITE (CAS 14464-46-1) Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

QUARTZ (SIO2) (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be **Chronic effects**

harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data available. Bioaccumulative potential

No data available. Mobility in soil

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

No data is available on the degradability of this product.

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

SDS US

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

CRISTOBALITE (CAS 14464-46-1) QUARTZ (SIO2) (CAS 14808-60-7) Cancer CRISTOBALITE (CAS 14464-46-1) lung effects QUARTZ (SIO2) (CAS 14808-60-7) lung effects

CRISTOBALITE (CAS 14464-46-1) immune system effects QUARTZ (SIO2) (CAS 14808-60-7) immune system effects

CRISTOBALITE (CAS 14464-46-1) kidney effects QUARTZ (SIO2) (CAS 14808-60-7) kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

Food and Drug Total food additive Administration (FDA) Direct food additive

GRAS food additive

US state regulations

California Proposition 65



WARNING: This product can expose you to QUARTZ (SIO2), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

QUARTZ (SIO2) (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

CRISTOBALITE (CAS 14464-46-1) QUARTZ (SIO2) (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical	No

Substances (EINECS)

European List of Notified Chemical Substances (ELINCS) Europe No Japan Inventory of Existing and New Chemical Substances (ENCS) No Korea Existing Chemicals List (ECL) No New Zealand New Zealand Inventory No **Philippines** Nο

Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) No United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory No

16. Other information, including date of preparation or last revision

19-July-2018 Issue date 25-October-2018 **Revision date**

Version # 24

HMIS® ratings Health: 3*

Flammability: 0 Physical hazard: 0

Health: 2 NFPA ratings

Flammability: 0 Instability: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and

completeness of such information for each particular use.

The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, CETCO, an MTI Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best

knowledge and experience currently available.

Hazard(s) identification: Prevention **Revision information**

First-aid measures: Inhalation

Handling and storage: Conditions for safe storage, including any incompatibilities

Exposure controls/personal protection: Eye/face protection Exposure controls/personal protection: Hand protection Exposure controls/personal protection: Respiratory protection

Exposure controls/personal protection: Other Stability and reactivity: Conditions to avoid Regulatory information: US state regulations

Other information, including date of preparation or last revision: References

GHS: Classification

Material name: VOLCLAY® BENTONITE

SDS US

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).