

SORBOND® UP

THICKENING/SOLIDIFYING AGENT

A powdered, clay based stabilization media used for the fixation of free liquids in sludge. Sorbond® UP is made from a nonbiodegradable mineral that is designed for use on waste that fails the Paint Filter Liquids Test (PFLT).



TECHNICAL SPECIFICATIONS

CHARACTERISTICS		PARTICLE	
		US Standard Sieve Size	% Retained
Color	Beige	30 mesh	0
Moisture Content	6-9%	50 mesh	0
Bulk Density (lbs/ft³)	70±2	70 mesh	0
pH (5% dispersion):	9.0-11.0	100 mesh	1.4
Package sizes available:	50lb. bags & 2,000lb. bulk bags	200 mesh	17.7
		-200 mesh	80.9
FUNCTION		TYPICAL ABSORPTION RATIO BY WEIGHT (ABSORBENT:WATER)	
Solidification of general wastes ranging pH 2-12		Up to 1:9	

cetco@mineralstech.com | cetco.com | 800.527.9948

UPDATED: DECEMBER 2020

© 2020 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.cetco.com. CETCO accepts no responsibility for the results obtained through application of this product. CETCO reserves the right to update information without notice.

