



**BUILDING MATERIALS GROUP**

1500 West Shure Drive  
Arlington Heights, Illinois 60004  
(800) 527-9948 Fax: (847) 506-6195  
www.cetco.com

April 15, 2005

## **LDC60® FLUID APPLIED WATERPROOFING LEED™ PRODUCT INFORMATION**

LDC 60 waterproofing membrane is a single-component, moisture cure urethane membrane. LDC60 is available in two grades, V and H, for vertical and horizontal applications.

### **MANUFACTURING LOCATION**

CETCO certifies that LDC60 is manufactured in Cleveland, OH. If your project falls within a 500-mile radius of this location, the product is considered to be a locally produced material and can help contribute to earning Materials & Resources - Credit 5.1.

### **RECYCLED CONTENT**

CETCO certifies that LDC60 is manufactured with a minimal percentage of post-consumer material recycled content (0.40% by weight) and post-industrial recycled content (2% by weight) from ordinary recovery of raw materials in manufacturing processes. Please note that this recycled content figures are not absolute. Day to day variations in manufacturing operations will result in minimal variations from the above listed figure. The product's recycled content by weight, LDC60 can help to contribute to earning Materials & Resources - Credit 4.1.

### **VOC CONTENT**

CETCO certifies that LDC60 contains <250 g/L Volatile Organic Compounds (VOCs).

CETCO is committed to the use of recycled content in the manufacturing of Volclay waterproofing products and supports the United States Green Building Council (USGBC) by participating as an USGBC Industry Member.

Sincerely,

A handwritten signature in black ink, appearing to read 'Stacy Byrd'.

Stacy Byrd  
National Products Manager



"LEED" is a trademark of the U.S. Green Building Council