

# SAFETY DATA SHEET

#### 1. Identification

Product identifier LIQUID BOOT LT COMPOUND A

Other means of identification Not available.

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

**Company name** CETCO, an MTI Company **Address** 2870 Forbs Avenue

Hoffman Estates, IL 60192

**United States** 

**Telephone** General Information 800 527-9948

Website www.cetco.com
E-mail safetydata@amcol.com

Emergency phone number

Americas 1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962

## 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 2

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Suspected of causing cancer.

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection.

**Response** If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information Not applicable.

#### 3. Composition/information on ingredients

## **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
ASPHALT	PETROLEUM ASPHALT	8052-42-4	40 - < 50
Hydrogen sulfide		7783-06-4	< 1
SODIUM HYDROXIDE		1310-73-2	< 1
Other components below reportable levels			50 - < 60

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Material name: LIQUID BOOT LT COMPOUND A

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact** Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

15619 Version #: 01 Revision date: 04-December-2014 Print date: 04-December-2014

Most important symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

**General information** 

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

### 5. Fire-fighting measures

Suitable extinguishing media

Foam. Dry powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions

Move containers from fire area if you can do so without risk.

**Specific methods** Move containers from fire area if you can do so without risk.

General fire hazards No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

#### 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store in a cool, dry place out of direct sunlight. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

#### Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
SODIUM HYDROXIDE (CAS 1310-73-2) US. OSHA Table Z-2 (29 CFR 1910.	PEL .1000)	2 mg/m3	
Components	Туре	Value	
Hydrogen sulfide (CAS 7783-06-4)	Ceiling	20 ppm	
US. ACGIH Threshold Limit Values	•		
Components	Туре	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fraction.
Hydrogen sulfide (CAS 7783-06-4)	STEL	5 ppm	
•	TWA	1 ppm	

US. ACGIH Threshold Limit Values				
Components	Туре	Value	Form	
SODIUM HYDROXIDE	Ceiling	2 mg/m3		

(CAS 1310-73-2)

**US. NIOSH: Pocket Guide to Chemical Hazards** Form Components Value ASPHALT (CAS 8052-42-4) Ceiling 5 mg/m3 Fume. Hydrogen sulfide (CAS Ceiling 15 mg/m3 7783-06-4) 10 ppm SODIUM HYDROXIDE 2 mg/m3 Ceiling (CAS 1310-73-2)

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protectionWear safety glasses with side shields (or goggles).Hand protectionUse personal protective equipment as required.OtherUse personal protective equipment as required.

**Respiratory protection** When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**General hygiene**considerations
Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

### 9. Physical and chemical properties

**Appearance** 

Physical stateLiquid.FormLiquid.ColorNot available.

Odor Not available.
Odor threshold Not available.
pH Not available.

Melting point/freezing point 86 °F (30 °C) estimated Initial boiling point and boiling 700 °F (371.11 °C) estimated

range

Flash point 283.7 °F (139.8 °C) estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0 hPa estimated

Vapor density Not available.

Relative density Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 905 °F (485 °C) estimated

**Decomposition temperature** Not available.

Not available. **Viscosity** 

Other information

Density 1.06 g/cm3 estimated Flammability class Combustible IIIB estimated

34.22 % estimated Percent volatile Specific gravity 1.06 estimated

#### 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability** Hazardous polymerization does not occur. Possibility of hazardous

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Not available.

## 11. Toxicological information

## Information on likely routes of exposure

Ingestion Expected to be a low ingestion hazard. Inhalation Prolonged inhalation may be harmful.

0---

Skin contact Not available.

Eye contact Direct contact with eyes may cause temporary irritation. Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Information on toxicological effects

Acute toxicity Componente

Components	Species	Test Results
Hydrogen sulfide (CAS 77	783-06-4)	
Acute		
Inhalation		
LC50	Monkey	0.7 mg/l, 35 Minutes
	Mouse	> 0.024 mg/l, 960 Minutes
		1.5 mg/l, 18 Minutes
		0.38 mg/l, 410 Minutes
		0.096 mg/l, 804 Minutes
	Rat	> 0.38 mg/l, 960 Minutes
		1.5 mg/l, 14 Minutes
		0.701 mg/l/4h
SODIUM HYDROXIDE (C	CAS 1310-73-2)	
A . 4 .		

T--4 D-----

Acute

Dermal

LD50 Rabbit 1350 mg/kg

Other

LD50 Mouse 40 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation. Serious eye damage/eye

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

#### Carcinogenicity

Suspected of causing cancer. This material contains petroleum asphalt. IARC has determined that there is inadequate evidence that undiluted, air-refined asphalt is carcinogenic to animals. There is only limited evidence that undiluted, steam-refined and cracking-residue asphalt are carcinogenic to animals. Additionally, IARC has concluded that there is inadequate evidence that asphalts alone are carcinogenic to humans.

Condensed asphalt fumes, which are generated under laboratory conditions and are chemically different from those found during typical asphalt operations, have been reported to cause bacterial mutations. However, inhalation of asphalt fumes by laboratory animals, during controlled studies, did not produce lung cancer. Additionally, human studies have not established a link between lung cancer and asphalt fume exposure to date. This product may contain trace amounts of polynuclear aromatic hydrocarbons (PAHs) as naturally occurring constituents of crude oils from which asphalt is derived. Some PAHs have been shown to be carcinogenic after prolonged or repeated skin contact in laboratory animals.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4)

2B Possibly carcinogenic to humans.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

Not classified.

single exposure

Specific target organ toxicity -

repeated exposure

Not classified.

Not available.

**Aspiration hazard** 

**Chronic effects** 

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

#### 12. Ecological information

**Ecotoxicity** 

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Hydrogen sulfide (CA	S 7783-06-4)		
Fish	LC50	Fish	0.0448 mg/L, 96 Hours
Aquatic			
Fish	LC50	Northern pike (Esox lucius)	0.009 mg/l, 96 hours
SODIUM HYDROXID	E (CAS 1310-73-2)		
Fish	LC50	Fish	45.4 mg/L, 96 Hours
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	34.59 - 47.13 mg/l, 48 hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

No data available. Bioaccumulative potential Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material **Disposal instructions** 

and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

## **US RCRA Hazardous Waste U List: Reference**

Hydrogen sulfide (CAS 7783-06-4)

U135

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

Material name: LIQUID BOOT LT COMPOUND A

SDS US 15619 Version #: 01 Revision date: 04-December-2014 Print date: 04-December-2014

#### 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

ASPHALT (CAS 8052-42-4) LISTED Hydrogen sulfide (CAS 7783-06-4) LISTED SODIUM HYDROXIDE (CAS 1310-73-2) LISTED

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

US EPCRA Section 304 Extremely Haz. Subs. & CERCLA Haz. Subs.: Section 304 EHS reportable quantity

Hydrogen sulfide (CAS 7783-06-4) 100 LBS

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Yes

Yes

Immediate Hazard - No **Hazard categories** 

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

**SARA 302 Extremely** 

hazardous substance

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

**Chemical name CAS** number % by wt. 7783-06-4 Hydrogen sulfide < 1

### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Hydrogen sulfide (CAS 7783-06-4) Safe Drinking Water Act

Not regulated.

(SDWA)

**US state regulations** 

US - Pennsylvania RTK - Hazardous Substances: Listed substance

Hydrogen sulfide (CAS 7783-06-4) SODIUM HYDROXIDE (CAS 1310-73-2)

US. Massachusetts RTK - Substance List

ASPHALT (CAS 8052-42-4) Hydrogen sulfide (CAS 7783-06-4) SODIUM HYDROXIDE (CAS 1310-73-2)

US. New Jersey Worker and Community Right-to-Know Act

Hydrogen sulfide (CAS 7783-06-4) 500 LBS

**US. Rhode Island RTK** 

Hydrogen sulfide (CAS 7783-06-4) SODIUM HYDROXIDE (CAS 1310-73-2)

**US. California Proposition 65** 

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT (CAS 8052-42-4) Listed: January 1, 1990

Material name: LIQUID BOOT LT COMPOUND A

SDS US

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

## 16. Other information, including date of preparation or last revision

Issue date 04-December-2014

Version # 01

United States & Puerto Rico

HMIS® ratings Health: 2\*

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 1 Instability: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and completeness of such information for each particular use.

The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience

currently available.

Yes