

SAFETY DATA SHEET

1. Identification

Product identifier ULTRASEAL® BT
Other means of identification Not available.

Recommended use Not available.

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name CETCO

Address 2870 Forbs Avenue

Hoffman Estates, IL 60192

United States

Telephone General Information 800 527-9948

Website http://www.cetco.com/
E-mail safety.data@amcol.com

Emergency phone number

Americas 1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ACRYLIC RESIN		9003-01-4	26
Other components below reportable levels			74

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Composition comments Occupational Exposure Limits for constituents are listed in Section 8. This product contains

naturally occurring crystalline silica (not listed in Annex I of Directive 67/548/EEC) in quantities less

than 3%.

4. First-aid measures

Inhalation Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel.

Get medical attention, if needed.

Skin contact Get medical attention if irritation develops or persists. No special measures required.

Eye contact Flush eyes immediately with large amounts of water. If irritation persists get medical attention. **Ingestion** If ingestion of a large amount does occur, seek medical attention. No special measures required.

Material name: ULTRASEAL® BT SDS US

4361 Version #: 13 Revision date: 19-July-2014 Print date: 21-July-2014

Most important symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Dry chemical, CO2, water spray or regular foam. Carbon dioxide (CO2). Use any media suitable for the surrounding fires.

Unsuitable extinguishing

media

None known.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Material can be slippery when wet.

Fire-fighting

equipment/instructions

In the event of fire, cool tanks with water spray.

Specific methods Cool containers exposed to flames with water until well after the fire is out.

General fire hazards Not a fire hazard. No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Material can be slippery when wet. Wear a dust mask if dust is generated above exposure limits. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This product is miscible in water. Stop the flow of material, if this is without risk. Collect dust or particulates using a vacuum cleaner with a HEPA filter. Avoid the generation of dusts during clean-up. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS. Reduce airborne dust and prevent scattering by moistening with water.

Environmental precautions No special environmental precautions required.

7. Handling and storage

Precautions for safe handling

Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

No special restrictions on storage with other products. Store in original tightly closed container. Store in a dry place. Store away from incompatible materials (see Section 10 of the SDS). Guard against dust accumulation of this material. Keep in a cool, well-ventilated place.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Constituents Value Form				
Constituents	Туре	value	1 01111	
INERT OR NUISANCE DUSTS (CAS SEQ250)	PEL	5 mg/m3	Respirable fraction.	
(CAS SEQ250)		15 mg/m3	Total dust.	
US. OSHA Table Z-3 (29 C	ED 1010 1000)	13 mg/m3	Total dust.	
Constituents	Type	Value	Form	
INERT OR NUISANCE DUSTS (CAS SEQ250)	TWA	5 mg/m3	Respirable fraction.	
(0.12 0 = 4 = 0)		15 mg/m3	Total dust.	
		50 millions of particle	Total dust.	
		15 millions of particle	Respirable fraction.	
US. ACGIH Threshold Lim	it Values			
Constituents	Туре	Value	Form	
INERT OR NUISANCE DUSTS	TWA	3 mg/m3	Respirable particles.	
(CAS SEQ250)		10 mg/m3	Inhalable particles.	
logical limit values	No higherical exposure limits noted for the ing	•	malable particles.	
Jyicai illilli values	No biological exposure limits noted for the ingredient(s).			

Bio

Exposure guidelines Some of the components of this product are hazardous in the respirable form. However, because

of the physical nature of this product, dust generation is not expected.

Appropriate engineering

controls

If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits. If engineering

measures are not sufficient to maintain concentrations of dust particulates below the OEL, suitable

respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear dust goggles. Avoid contact with eyes. Eye wash fountain is recommended.

Hand protection For prolonged or repeated skin contact use suitable protective gloves.

Other No special protective equipment required.

Respiratory protectionUse a particulate filter respirator for particulate concentrations exceeding the Occupational

Exposure Limit.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene Use good industrial hygiene practices in handling this material.

considerations

9. Physical and chemical properties

Appearance The product consists of bentonite granules between geotextile layers

Physical stateSolid.FormSolid.

ColorNot available.OdorNot available.Odor thresholdNot available.

pH 7 - 11

7 - 11

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point Non-flammable
Evaporation rate Not available.
Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Non-explosive

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0 hPa estimated

Vapor density Not available.
Relative density Not available.

Solubility(ies)

Solubility (water) Negligible

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Percent volatile 0 % estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Stable at normal conditions.

Possibility of hazardous

reactions

Will not occur.

Conditions to avoidNone known. Contact with incompatible materials.

Incompatible materials None known.

Material name: ULTRASEAL® BT 4361 Version #: 13 Revision date: 19-July-2014 Print date: 21-July-2014 **Hazardous decomposition**

products

None known.

11. Toxicological information

Information on likely routes of exposure

Ingestion Expected to be a low ingestion hazard.

Inhalation No adverse effects due to inhalation are expected.

Skin contact Not available.

Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms related to the Direct contact with eyes may cause temporary irritation.

physical, chemical and toxicological characteristics

Information on toxicological effects

Acute toxicity

Components Species Test Results

ACRYLIC RESIN (CAS 9003-01-4)

Acute

Oral

LD50 Rat 2500 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Mild irrit

irritation

Mild irritant to eyes (according to the modified Kay & Calandra criteria) Mild irritant to eyes

(according to the modified Kay & Calandra criteria)

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization According to the classification criteria of the European Union, the product is not considered as

being a skin irritant.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded

that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art,

worker protection against silicosis can be consistently assured by respecting the existing

regulatory occupational exposure limits. Occupational exposure to respirable dust and respirable

crystalline silica should be monitored and controlled.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not available.

Material name: ULTRASEAL® BT
4361 Version #: 13 Revision date: 19-July-2014 Print date: 21-July-2014

Chronic effects

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)

In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)

According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Some of the components of this product are hazardous in the respirable form. However, because of the physical nature of this product, dust generation is not expected.

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

12. Ecological information

Ecotoxicity

This material is not expected to be harmful to aquatic life.

Components		Species	Test Results
ACRYLIC RESIN (C	AS 9003-01-4)		
Fish	LC50	Fish	580 mg/L, 96 Hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in

accordance with all applicable regulations. Material should be recycled if possible.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations

OSHA Process Safety Standard: This material is not known to be hazardous by the OSHA Highly Hazardous Process Safety Standard, 29 CFR 1910.119.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Material name: ULTRASEAL® BT

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - No **Hazard categories**

> Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

WARNING: This product contains a chemical known to the State of California to cause cancer. **US state regulations**

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Inventory name

Not regulated.

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region

Country(s) or region	inventory name	On inventory (yes/no)
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

21-July-2014 Issue date **Revision date** 21-July-2014

Version # 13

United States & Puerto Rico

This safety datasheet only contains information relating to safety and does not replace any product **Further information**

information or product specification.

HMIS® ratings Health: 1*

Flammability: 0 Physical hazard: 0

Material name: ULTRASEAL® BT 4361 Version #: 13 Revision date: 19-July-2014 Print date: 21-July-2014 Yes

On inventory (ves/no)*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

NFPA ratings

Disclaimer

Health: 1 Flammability: 0 Instability: 0

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and completeness of such information for each particular use.

Third party materials: Insofar as materials not manufactured or supplied by this manufacturer are used in conjunction with, or instead of this product, it is the responsibility of the customer to obtain, from the manufacturer or supplier, all technical data and other properties relating to these and other materials and to obtain all necessary information relating to them. No liability can be accepted in respect of the use of this product in conjunction with materials from another supplier. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.

Material name: ULTRASEAL® BT
4361 Version #: 13 Revision date: 19-July-2014 Print date: 21-July-2014