



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Material name VOLCLAY® PANEL TYPE-1
Version # 04
Revision date 24-February-2011
CAS # Mixture
Manufacturer information CETCO
Building Materials Group
2870 Forbs Avenue
Hoffman Estates, IL 60192 US
safety.data@amcol.com
http://www.cetco.com/
General Information (800) 527-9948
CHEMTREC® (800) 424-9300

2. Hazards Identification

Emergency overview This product has the potential for generation of respirable dust during handling and use. Dust may contain respirable crystalline silica.

Potential health effects

Routes of exposure Inhalation. Eye contact.

Eyes Dust or powder may irritate eye tissue.

Skin Non-irritating to the skin.

Inhalation Repeated or prolonged inhalation may cause toxic effects. For additional information on inhalation hazards, see Section 11 of this safety data sheet.

Ingestion No hazard in normal industrial use. No significant adverse effects are expected upon ingestion of the product.

Target organs Lungs.

Chronic effects Overexposure to dust may result in pneumoconiosis, a respiratory disease caused by inhalation of mineral dust, which can lead to fibrotic changes to the lung tissue, or silicosis, a respiratory disease caused by inhalation of silica dust, which can lead to inflammation and fibrosis of the lung tissue. Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

3. Composition / Information on Ingredients

Components	CAS #	Percent
BENTONITE	1302-78-9	60 - 100

Composition comments Bentonite contains naturally occurring crystalline silica (not listed in Annex I of Directive 67/548/EEC) in quantities less than 6%. Occupational Exposure Limits for impurities are listed in Section 8.

4. First Aid Measures

First aid procedures

Eye contact Flush eyes immediately with large amounts of water. Get medical attention if irritation develops or persists.

Skin contact No special measures required. Get medical attention if irritation develops or persists.

Inhalation If symptoms are experienced, remove source of contamination or move victim to fresh air. If the affected person is not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Call a physician if symptoms develop or persist.

Ingestion No special measures required. If ingestion of a large amount does occur, seek medical attention.

Notes to physician Provide general supportive measures and treat symptomatically.

5. Fire Fighting Measures

Flammable properties None known.

Extinguishing media

Suitable extinguishing media Use any media suitable for the surrounding fires. Dry chemical, CO2, water spray or regular foam.

Protection of firefighters

Protective equipment for firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Fire fighting equipment/instructions Not available.

Hazardous combustion products None known.

6. Accidental Release Measures

Personal precautions Wear a dust mask if dust is generated above exposure limits.

Environmental precautions No special environmental precautions required.

Methods for containment None necessary.

Methods for cleaning up Avoid the generation of dusts during clean-up. Collect dust or particulates using a vacuum cleaner with a HEPA filter. Reduce airborne dust and prevent scattering by moistening with water.

7. Handling and Storage

Handling Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. In case of insufficient ventilation, wear suitable respiratory equipment.

Storage Guard against dust accumulation of this material. No special storage conditions required. No special restrictions on storage with other products.

8. Exposure Controls / Personal Protection

Occupational exposure limits

Canada - British Columbia

Impurities	Type	Value	Form
INERT OR NUISANCE DUST (SEQ250)	TWA	3.0000 mg/m3	Respirable fraction.
		10.0000 mg/m3	Total dust.
QUARTZ (14808-60-7)	TWA	0.0250 mg/m3	Respirable fraction.

Canada - Ontario

Impurities	Type	Value	Form
INERT OR NUISANCE DUST (SEQ250)	TWA	10.0000 mg/m3	Inhalable particulate.
		3.0000 mg/m3	Respirable particles.
QUARTZ (14808-60-7)	TWA	0.1000 mg/m3	Respirable fraction.

Canada - Quebec

Impurities	Type	Value	Form
INERT OR NUISANCE DUST (SEQ250)	TWA	10.0000 mg/m3	Total dust.
QUARTZ (14808-60-7)	TWA	0.1000 mg/m3	Respirable dust.

Exposure guidelines Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

Engineering controls If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits. If engineering measures are not sufficient to maintain concentrations of dust particulates below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Eye / face protection Wear dust goggles.

Skin protection No special protective equipment required.

Respiratory protection Use a particulate filter respirator for particulate concentrations exceeding the Occupational Exposure Limit.

9. Physical & Chemical Properties

Appearance Not available.

Color Various.

Odor None.

Odor threshold Not available.

Physical state	Not available.
Form	Panel
pH	Not available.
Melting point/Freezing point	Not available.
Boiling point	Not available.
Flash point	Not flammable
Evaporation rate	Not available.
Flammability limits in air, upper, % by volume	Not explosive
Flammability limits in air, lower, % by volume	Not explosive
Vapor pressure	Not available.
Vapor density	Not available.
Specific gravity	Not available.
Relative density	Not available.
Solubility (water)	Negligible
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.

10. Chemical Stability & Reactivity Information

Chemical stability	Stable at normal conditions.
Conditions to avoid	None known.
Incompatible materials	None known.
Hazardous decomposition products	None known.
Possibility of hazardous reactions	Will not occur.

11. Toxicological Information

Toxicological data

Impurities

QUARTZ (14808-60-7)

Test Results

Acute Oral LD50 Rat: 500 mg/kg

Sensitization

No sensitization responses were observed.

Chronic effects

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)

In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)

According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

QUARTZ (CAS 14808-60-7)

1 Carcinogenic to humans.

12. Ecological Information

Ecotoxicological data

Product	Test Results
VOLCLAY® PANEL TYPE-1 (Mixture)	LC50 Fish: 22353 mg/l 96.00 Hours estimated
Components	Test Results
BENTONITE (1302-78-9)	LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss): 19000 mg/l 96.00 hours

Ecotoxicity	This product is not expected to produce significant ecotoxicity upon exposure to aquatic organisms and aquatic systems.
Environmental effects	Based on the physical properties of this product, significant environmental persistence and bioaccumulation would not be expected.
Persistence and degradability	Not available.

13. Disposal Considerations

Disposal instructions Dispose in accordance with all applicable regulations. Material should be recycled if possible.

14. Transport Information

TDG

Not regulated as dangerous goods.

15. Regulatory Information

WHMIS status	Controlled
WHMIS classification	D2A - Other Toxic Effects-VERY TOXIC
WHMIS labeling	



Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information


Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

Further information This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

HMIS ratings

HMIS®		
HEALTH	*	1
FLAMMABILITY		0
PHYSICAL HAZARD		0
PERSONAL PROTECTION		

NFPA ratings



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and completeness of such information for each particular use.

Third party materials: Insofar as materials not manufactured or supplied by this manufacturer are used in conjunction with, or instead of this product, it is the responsibility of the customer to obtain, from the manufacturer or supplier, all technical data and other properties relating to these and other materials and to obtain all necessary information relating to them. No liability can be accepted in respect of the use of this product in conjunction with materials from another supplier. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Prepared by

EHS Department

Issue date

24-February-2011