

SAFETY DATA SHEET

1. Identification

Product identifier XP POLY-ADH MIX

Other means of identificationNot available.Recommended useNot available.Recommended restrictionsNone known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name CETCO, an MTI Company

Address 2870 Forbs Avenue

Hoffman Estates, IL 60192

United States

Telephone General Information 800 527-9948

Website http://www.cetco.com/
E-mail safety.data@amcol.com

Emergency phone number

Americas 1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962 Access Code 333562

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical	name	Common name and synonyms	CAS number	%
VINYL AC	ETATE		108-05-4	0.0004999999
Other com	nponents below reportable lev	els		99.9994999999

Residuals

Chemical name CAS number %

Acrylamide 79-06-1

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Composition comments Occupational Exposure Limits for impurities are listed in Section 8. Occupational Exposure Limits

for residuals are listed in Section 8.

4. First-aid measures

Inhalation If dust from the material is inhaled, remove the affected person immediately to fresh air. If

symptoms are experienced, remove source of contamination or move victim to fresh air. Call a

physician if symptoms develop or persist.

Skin contact Wash affected area with mild soap and water. Get medical attention if irritation develops or

persists

Material name: XP POLY-ADH MIX

5453 Version #: 04 Revision date: 07-May-2015 Print date: 07-May-2015

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists get medical

attention

Ingestion For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get

Direct contact with eyes may cause temporary irritation.

medical attention.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

General information

Provide general supportive measures and treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Dry chemical, CO2, water spray or regular foam. Carbon

dioxide (CO2). None known.

Unsuitable extinguishing

media

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Fire-fighting

equipment/instructions

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. In the event of fire, cool tanks with water spray.

Material can be slippery when wet..

Specific methodsCool containers exposed to flames with water until well after the fire is out.

General fire hazards Not a fire hazard. No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Avoid inhalation of dust from the spilled material. For personal protection, see section 8 of the SDS. Material can be slippery when

we

Methods and materials for containment and cleaning up

Stop leak if you can do so without risk. Sweep up or gather material and place in appropriate container for disposal. After removal flush contaminated area thoroughly with water. If sweeping of a contaminated area is necessary use a dust suppressant agent which does not react with the product. Sweep up or vacuum up spillage and collect in suitable container for disposal. Collect dust using a vacuum cleaner equipped with HEPA filter. Minimize dust generation and accumulation. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

No special environmental precautions required.

7. Handling and storage

Precautions for safe handling

Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Wash hands after handling and before eating. Do not get this material in contact with eyes. Avoid breathing dust. Avoid contact with skin and eyes. Avoid prolonged exposure. In case of insufficient ventilation, wear suitable respiratory equipment. Practice good housekeeping.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Keep containers tightly closed in a cool, well-ventilated place. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Guard against dust accumulation of this material.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Impurities	Type	Value	Form
INERT OR NUISANCE DUSTS (CAS SEQ250)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Residuals	Туре	Value	
Acrylamide (CAS 79-06-1)	PEL	0.3 mg/m3	

Material name: XP POLY-ADH MIX 5453 Version #: 04 Revision date: 07-May-2015 Print date: 07-May-2015

US. OSHA Table Z-3 (29 CFR 1910.1000)

Impurities	Туре	Value	Form
INERT OR NUISANCE DUSTS (CAS SEQ250)	TWA	5 mg/m3	Respirable fraction.
,		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Value	s		
Components	Туре	Value	
VINYL ACETATE (CAS 108-05-4)	STEL	15 ppm	
,	TWA	10 ppm	
Residuals	Туре	Value	Form
Acrylamide (CAS 79-06-1)	TWA	0.03 mg/m3	Inhalable fraction and vapor.
US. NIOSH: Pocket Guide to Cher	nical Hazards		
Components	Туре	Value	
VINYL ACETATE (CAS 108-05-4)	Ceiling	15 mg/m3	
,		4 ppm	
Residuals	Туре	Value	
Acrylamide (CAS 79-06-1)	TWA	0.03 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

Acrylamide (CAS 79-06-1) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Acrylamide (CAS 79-06-1) Skin designation applies.

US - Tennesse OELs: Skin designation

Acrylamide (CAS 79-06-1) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Acrylamide (CAS 79-06-1) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Acrylamide (CAS 79-06-1)

Can be absorbed through the skin.

US OSHA Table Z-1: Skin designation

Acrylamide (CAS 79-06-1) Can be absorbed through the skin.

Appropriate engineering controls

Ventilation should be sufficient to effectively remove and prevent buildup of any dusts or fumes that may be generated during handling or thermal processing. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If engineering measures are not sufficient to maintain concentrations of dust particulates below the OEL, suitable respiratory protection must be

worn.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear chemical goggles. Use tight fitting goggles if dust is generated. **Hand protection** For prolonged or repeated skin contact use suitable protective gloves.

Other Normal work clothing (long sleeved shirts and long pants) is recommended. Wear appropriate

chemical resistant gloves.

Respiratory protection Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels

exceeding the exposure limits. If airborne concentrations are above the applicable exposure limits,

use NIOSH approved respiratory protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Use good industrial hygiene practices in handling this

material.

Material name: XP POLY-ADH MIX

9. Physical and chemical properties

Granular. **Appearance** Solid. Physical state Powder. **Form** Color White. None. Odor

Odor threshold Not available. Not available. pН Not available. Melting point/freezing point Not available. Initial boiling point and boiling

range

Not available. Flash point Not available. **Evaporation rate** Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

Not available.

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available. Not available. Vapor pressure Not available. Vapor density Not available. Relative density

Solubility(ies)

Solubility (water) Not available. Not available. Partition coefficient

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Not available. **Viscosity**

Other information

Density 0.93 g/cm3 estimated

Percent volatile 0 % estimated Specific gravity 0.93 estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Stable at normal conditions. **Chemical stability**

Possibility of hazardous

reactions

Will not occur.

None known. Contact with incompatible materials. Avoid dispersal of dust in the air (i.e., clearing Conditions to avoid

dust surfaces with compressed air).

Incompatible materials None known.

Hazardous decomposition

products

At thermal decomposition temperatures, carbon monoxide and carbon dioxide.

11. Toxicological information

Information on likely routes of exposure

Ingestion Expected to be a low ingestion hazard.

Inhalation Prolonged inhalation may be harmful. Inhalation of dusts may cause respiratory irritation.

Not available. Skin contact

Dust in the eyes will cause irritation. Eye contact

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Material name: XP POLY-ADH MIX 5453 Version #: 04 Revision date: 07-May-2015 Print date: 07-May-2015

Acute toxicity				
Components	Species	Test Results		
VINYL ACETATE (CAS 108-05-4	4)			
Acute				
Dermal				
LD50	Rabbit	2320 mg/kg		
Inhalation				
LC50	Guinea pig	6215 ppm, 4 Hours		
	Mouse	1550 ppm, 4 Hours		
	Rabbit	2500 ppm, 4 Hours		
	Rat	3680 ppm, 4 Hours		
		11.4 mg/l/4h		
Oral				
LD50	Mouse	1613 mg/kg		
	Rat	2920 mg/kg		
Other				
LD50	Mouse	595 mg/kg		
Residuals	Species	Test Results		
Acrylamide (CAS 79-06-1)	•			
Acute				
Dermal				
LD50	Rabbit	1.68 ml/kg		
	Rat	400 mg/kg		
		1.68 ml/kg		
Oral				
LD50	Mouse	107 mg/kg		
	Rabbit	150 mg/kg		
	Rat	124 mg/kg		
Other		3 3		
LD50	Guinea pig	170 mg/kg		
	Mouse	170 mg/kg		
	Rat	90 mg/kg		
	Nat	50 mg/kg		
* Estimates for product may	be based on additional component data not	shown.		
Skin corrosion/irritation	Prolonged skin contact may cause temp	Prolonged skin contact may cause temporary irritation.		
Serious eye damage/eye irritation	Dust in the eyes will cause irritation.			
Respiratory or skin sensitization	on			
Respiratory sensitization	Not available.			

Skin sensitization No skin irritation

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Acrylamide (CAS 79-06-1) 2A Probably carcinogenic to humans. VINYL ACETATE (CAS 108-05-4) 2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Reasonably Anticipated to be a Human Carcinogen. Acrylamide (CAS 79-06-1)

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not available.

Material name: XP POLY-ADH MIX

SDS US 5453 Version #: 04 Revision date: 07-May-2015 Print date: 07-May-2015

Prolonged inhalation may be harmful. Overexposure to dusts may result in pneumoconiosis, a lung disease due to permanent deposition of substantial amounts of particulate matter in the lungs.

12. Ecological information

Ecotoxicity

This material is not expected to be harmful to aquatic life.

Components		Species	Test Results
VINYL ACETATE (CA	S 108-05-4)		
Fish	LC50	Fish	31 mg/L, 96 Hours
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	15.04 - 21.54 mg/l, 96 hours
Residuals		Species	Test Results
Acrylamide (CAS 79-0	06-1)		
Crustacea	EC50	Daphnia	98 mg/L, 48 Hours
Fish	LC50	Fish	109 mg/L, 96 Hours
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	81 - 150 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability

Not inherently biodegradable.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

VINYL ACETATE 0.73 Acrylamide -0.67

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in

accordance with all applicable regulations.

Local disposal regulationsDispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

US RCRA Hazardous Waste U List: Reference

Acrylamide (CAS 79-06-1) U007

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations OSHA Process Safety Standard: This material is not known to be hazardous by the OSHA Highly

Hazardous Process Safety Standard, 29 CFR 1910.119.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acrylamide (CAS 79-06-1)

VINYL ACETATE (CAS 108-05-4)

LISTED

LISTED

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Material name: XP POLY-ADH MIX
5453 Version #: 04 Revision date: 07-May-2015 Print date: 07-May-2015

US EPCRA Section 304 Extremely Haz. Subs. & CERCLA Haz. Subs.: Section 304 EHS reportable quantity

Acrylamide (CAS 79-06-1) 5000 LBS VINYL ACETATE (CAS 108-05-4) 5000 LBS

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely

No

hazardous substance

No

chemical

SARA 313 (TRI reporting)

SARA 311/312 Hazardous

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Acrylamide (CAS 79-06-1)

VINYL ACETATE (CAS 108-05-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

VINYL ACETATE (CAS 108-05-4)

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

US - Pennsylvania RTK - Hazardous Substances: Listed substance

Acrylamide (CAS 79-06-1)
VINYL ACETATE (CAS 108-05-4)
Massachusetts RTK - Substance List

US. Massachusetts RTK - Substance List

Acrylamide (CAS 79-06-1) VINYL ACETATE (CAS 108-05-4)

US. New Jersey Worker and Community Right-to-Know Act

Acrylamide (CAS 79-06-1) 500 LBS VINYL ACETATE (CAS 108-05-4) 500 LBS

US. Rhode Island RTK

Acrylamide (CAS 79-06-1) VINYL ACETATE (CAS 108-05-4)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Acrylamide (CAS 79-06-1) Listed: January 1, 1990

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Acrylamide (CAS 79-06-1) Listed: February 25, 2011

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Acrylamide (CAS 79-06-1) Listed: February 25, 2011

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

Material name: XP POLY-ADH MIX
5453 Version #: 04 Revision date: 07-May-2015 Print date: 07-May-2015

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 19-August-2014 **Revision date** 07-May-2015

Version # 04

Further information This safety datasheet only contains information relating to safety and does not replace any product

information or product specification.

HMIS® ratings Health: 1

Flammability: 0 Physical hazard: 0

NFPA ratings Health: 1

Flammability: 0 Instability: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and

completeness of such information for each particular use.

Third party materials: Insofar as materials not manufactured or supplied by this manufacturer are used in conjunction with, or instead of this product, it is the responsibility of the customer to obtain, from the manufacturer or supplier, all technical data and other properties relating to these and other materials and to obtain all necessary information relating to them. No liability can be accepted in respect of the use of this product in conjunction with materials from another supplier. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience

currently available.

Material name: XP POLY-ADH MIX