

ACCOFLOC® 361

FLOCCULANT AID



Bentonite flocculant aid for use in industrial and municipal treatment plants. Used in conjunction with polymers or other flocculating agents to aid in the removal of heavy metals, oils, and grease. When dispersed in a waste stream, ACCOFLOC® 361 attracts contaminants to help increase floc size and weight. Resulting floc increases treatment efficiency and improves sludge dewatering. ACCOFLOC® 361 is certified to NSF/ANSI/CAN Standard 60, Drinking Water Treatment Chemicals – Health Effects.



TECHNICAL SPECIFICATIONS			
CHARACTERISTICS		PARTICLE	
Color	Beige Fine Granular	US Standard Sieve Size	% Retained
Moisture Content	12%	10 mesh	25
Bulk Density (lbs/ft³)	55±2	40 mesh	98.5
pH (5% dispersion):	8.5–10.5	50 mesh	1.5
Package sizes available:	50lb. bags & 2,000lb. bulk bags		

cetco@mineralstech.com | cetco.com | 800.527.9948

UPDATED: SEPTEMBER 2025

© 2025 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.
FORM: TDS_ACCOFLOC 361_AM_EN_202509

