

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 9/11/2012 Revision date: 2/15/2023 Supersedes: 4/20/2020 Version: 2.3

SECTION 1: Identification		
1.1. Identification		
Product form Product name Product code Other means of identification	<ul> <li>Mixture</li> <li>Sericron® Talc</li> <li>C-MS-AT-2040SERICON</li> <li>SERICRON® 2M, SERICRON® 3M, SERICRON® 4M, SERICRON® 5M, SERICRON® 6M, SERICRON® W2M, SERICRON® 7M</li> </ul>	
1.2. Recommended use and restrictions on use		
Use of the substance/mixture Restrictions on use	<ul><li>Mineral additive</li><li>Anything other than the above</li></ul>	
1.3. Supplier		
Barretts Minerals Inc. 8625 Highway 91 South Dillon,. MT 59725 USA Telephone: 406-683-3323		
EU Supplier: Minteq Europe Ltd (Minteq International Inc.) Tivoli Industrial Estate Cork - Ireland Telephone: +353 21 4503241 - Fax: +353 21 450635 E-mail: sds@minteq.com	52	
1.4. Emergency telephone number		
Emergency number	<ul> <li>+1 760 476 3962</li> <li>3E Global Emergency Response Services. Access code: 333336 (if you mention SDS name and company name-you don't need the access code)</li> </ul>	
SECTION 2: Hazard(s) identification		
2.1. Classification of the substance or mixt	ure	
GHS US classification Carcinogenicity, Category 1A Specific target organ toxicity – Single exposure, Cate Full text of H-statements: see section 16	H350 May cause cancer (Inhalation). egory 1 H370 Causes damage to organs (lung/respiratory system) (Inhalation).	
2.2. GHS Label elements, including precaut	ionary statements	
GHS US labelling Hazard pictograms (GHS US)		
Signal word (GHS US) Hazard statements (GHS US)	<ul> <li>Danger</li> <li>H350 - May cause cancer (Inhalation).</li> <li>H370 - Causes damage to organs (lung/respiratory system) (Inhalation).</li> </ul>	

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US)	<ul> <li>P201 - Obtain special instructions before use.</li> <li>P202 - Do not handle until all safety precautions have been read and understood.</li> <li>P260 - Do not breathe dust.</li> <li>P264 - Wash hands, forearms and face thoroughly after handling.</li> <li>P270 - Do not eat, drink or smoke when using this product.</li> <li>P280 - Wear protective gloves, protective clothing, eye protection, face protection.</li> <li>P308+P313 - If exposed or concerned: Get medical advice/attention.</li> <li>P405 - Store locked up.</li> </ul>
2.3. Other hazards which do not result in cla	ssification
Other hazards which do not result in classification	: Dust may cause mechanical irritation of the eyes, skin and upper respiratory tract. Prolonged and/or massive exposure to respirable crystalline silica-containing dust may cause silicosis, a nodular pulmonary fibrosis caused by deposition in the lungs of fine respirable particles of crystalline silica.

### 2.4. Unknown acute toxicity (GHS US)

No additional information available

# **SECTION 3: Composition/information on ingredients**

## 3.1. Substances

### Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Talc	CAS-No.: 14807-96-6	50 - 80	Not classified
Chlorite-group minerals	CAS-No.: 1318-59-8	10 - 30	Not classified
Dolomite	CAS-No.: 16389-88-1	5 - 10	Not classified
Magnesite	CAS-No.: 7760-50-1	1 - 5	Not classified
Calcite	CAS-No.: 1317-65-3	1 - 5	Not classified
Quartz	CAS-No.: 14808-60-7	0.1 – 1	Carc. 1A, H350 STOT SE 3, H335 STOT SE 1, H370

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret Full text of hazard classes and H-statements : see section 16

### **SECTION 4: First-aid measures**

4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If symptoms develop, obtain medical attention.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If symptoms develop, obtain medical attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If symptoms develop, obtain medical attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Give 100 - 200 ml of water to drink. If symptoms develop, obtain medical attention.

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms and effects (acute and delayed)	
Potential adverse human health effects and symptoms	: Dust may cause mechanical irritation of the eyes, skin and upper respiratory tract. May cause cancer (if inhaled). May cause damage to organs (lungs) through prolonged or repeated exposure (Inhalation).
4.3. Immediate medical attention and special treatment, if necessary	

Treat symptomatically.

SECTION 5: Fire-fighting measures		
5.1. Suitable (and unsuitable) extinguis	shing media	
Suitable extinguishing media Unsuitable extinguishing media	<ul><li>Not combustible. Use extinguishing media appropriate for surrounding fire.</li><li>None known.</li></ul>	
5.2. Specific hazards arising from the o	chemical	
Fire hazard	: None known.	
5.3. Special protective equipment and	precautions for fire-fighters	
Protection during firefighting	: Fire fighters should wear complete protective clothing including self-contained breathing apparatus.	

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equ	ipment and emergency procedures	
6.1.1. For non-emergency personnel		
Protective equipment	: Use personal protective equipment as required.	
Emergency procedures	: Ventilate area. Avoid dust formation. Do not breathe dust. Avoid contact with eyes, skin and clothing. Evacuate unnecessary personnel.	
6.1.2. For emergency responders		
Protective equipment	: Wear suitable protective clothing, gloves and eye or face protection. Where excessive dust may result, wear approved mask.	
Emergency procedures	: Ventilate area. Avoid dust formation. Do not breathe dust. Wear independent breathing equipment. Avoid contact with skin, eyes and clothing.	
6.2. Environmental precautions		

Notify authorities if large amounts of the product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up		
Methods for cleaning up	: Minimise generation of dust. Do not dry sweep dust. Collect using vacuum cleaner fitted with HEPA filter. Dispose in a safe manner in accordance with local/national regulations.	

### 6.4. Reference to other sections

SECTION 8: Exposure controls/personal protection. SECTION 13: Disposal considerations.

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Precautions for safe handling :	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.	
7.2. Conditions for safe storage, including any	/ incompatibilities	
-	Keep container closed when not in use. None.	
SECTION 8: Exposure controls/personal	protection	
8.1. Control parameters		
Sericron® Talc		
No additional information available		
Talc (14807-96-6)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Talc	
ACGIH TWA (mg/m³)	2 mg/m <sup>3</sup> (Containing no asbestos fibers. E - The value is for particulate matter containing no asbestos and < 1 % crystalline silica, R - Respirable particulate matter) 2 mg/m <sup>3</sup> (Containing asbestos fibers. R - Respirable particulate matter)	
ACGIH TWA (ppm)	0.1 fibers/cm <sup>3</sup> (Containing asbestos fibers. F - Respirable fibers)	
Remark (ACGIH)	Containing no asbestos fibers = TLV® Basis: Pulm fibrosis; pulm func. Notations: A4 Containing asbestos fibers = TLV® Basis: Pneumoconiosis; lung cancer; mesothelioma. Notations: A1 (Confirmed Human Carcinogen)	
Regulatory reference	ACGIH 2022	
USA - OSHA - Occupational Exposure Limits		
Local name	Talc (not containing asbestos) (Silicates (less than 1% crystalline silica))	
OSHA PEL TWA [2]	20 mppcf	
Remark (OSHA)	Table Z-3. CAS No. source: eCFR Table Z-1.	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts	
Chlorite-group minerals (1318-59-8)		
No additional information available		
Dolomite (16389-88-1)		
No additional information available		
Quartz (14808-60-7)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Silica crystaline - quartz	
ACGIH TWA (mg/m³)	0.025 mg/m <sup>3</sup> (R - Respirable particulate matter)	

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Quartz (14808-60-7)	
Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2022
USA - OSHA - Occupational Exposure Limits	
Local name	Quartz (Respirable) (Silica: Crystalline)
OSHA PEL (TWA) (mg/m³)	0.05 mg/m³ [Action level: 0.025 mg/m³]
Remark (OSHA)	Table Z-3. For OSHA PEL (TWA): Use formulas: (250 / (%SiO2+5)) for mppcf and (10 mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
Magnesite (7760-50-1)	
No additional information available	
Calcite (1317-65-3)	
USA - OSHA - Occupational Exposure Limits	
Local name	Calcium Carbonate (Limestone; Marble)
OSHA PEL (TWA) (mg/m³)	15 mg/m <sup>3</sup> (Total dust) 5 mg/m <sup>3</sup> (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
8.2. Appropriate engineering controls	
Appropriate engineering controls	: Provide appropriate exhaust ventilation at places where dust is formed. Ensure exposure is below occupational exposure limits (where available). Local exhaust ventilation (LEV) may be required to control inhalation exposure.
Environmental exposure controls	: Avoid release to the environment.
8.3. Individual protection measures/Perso	onal protective equipment
Personal protective equipment: Avoid all unnecessary exposure.	
Hand protection:	
Wear chemically resistant protective gloves.	
Eye protection:	
Chemical goggles or safety glasses	
Skin and body protection:	
Use chemically protective clothing	
Respiratory protection:	
Dust mask or respirator	
Thermal hazard protection: Not required for normal conditions of use.	

### Other information:

Do not eat, drink or smoke during use.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: White. Powder.
Colour	: White
Odour	: None
Odour threshold	: No data available
рН	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Not flammable.
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: 2.8 (Water = 1)
Solubility	: Water: Insoluble
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: Not explosive.
Oxidising properties	: Not oxidising.

### 9.2. Other information

No additional information available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Stable under recommended handling and storage conditions (see section 7).

**10.2. Chemical stability** 

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

#### None known.

10.4. Conditions to avoid

### Dust formation.

10.5. Incompatible materials

None.

### 10.6. Hazardous decomposition products

None known.

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: Toxicological information	
11.1. Information on toxicological effects	
Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation)	<ul> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> </ul>
Talc (14807-96-6)	
LD50 oral, rat	> 5000 mg/kg (OECD 423 method)
Calcite (1317-65-3)	
LD50 oral, rat	> 5000 mg/kg
Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitisation Germ cell mutagenicity Carcinogenicity	<ul> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> <li>May cause cancer (Inhalation).</li> </ul>
Talc (14807-96-6)	
IARC group	3 - Not classifiable, 2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Not listed by NTP, ACGIH, OSHA, or NIOSH
Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: Not classified
Talc (14807-96-6)	
NOAEL (animal/female, F0/P)	> 900 mg/kg bodyweight/day rabbit (OECD 416 method)
STOT-single exposure	: Causes damage to organs (lung/respiratory system) (Inhalation).
Quartz (14808-60-7)	
STOT-single exposure	May cause respiratory irritation. Causes damage to organs (lungs) (Inhalation).
STOT-repeated exposure Aspiration hazard Viscosity, kinematic Potential adverse human health effects and symptoms	<ul> <li>Not classified</li> <li>Not classified</li> <li>No data available</li> <li>Dust may cause mechanical irritation of the eyes, skin and upper respiratory tract. May cause cancer (if inhaled). May cause damage to organs (lungs) through prolonged or repeated exposure (Inhalation).</li> </ul>

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information

: IARC: In 2006, IARC concluded that inhaled talc not containing asbestos or asbestiform fibers is not classifiable as a human carcinogen (Group 3). IARC concluded that there is limited evidence that the use of talc-based body powder for perineal dusting is a possible risk factor for ovarian cancer (Group 2B). This is not a route of exposure relevant to workers and applies only to one specific use of talc.

NTP: In 2000, NTP reviewed both "talc containing asbestiform fibers" and "talc not containing asbestiform fibers," and did not list either type in light of continuing uncertainty in the scientific literature. The NTP did not consider the ovarian cancer studies in the evaluation of talc not containing asbestiform fibers because it was unclear if the talc used in these studies might have been contaminated with asbestos. 66 Fed. Reg. 13,334 (Mar. 5, 2001).

U.S.FDA: In 2009 – 2010, U.S. FDA conducted a survey of currently marketed cosmetic products containing talc- as well as the talc in the cosmetic products, and found no asbestos fibers or structures. FDA continues to monitor new information concerning talc safety. There are epidemiology studies on this subject in the reported literature that should be consulted for further information.

## **SECTION 12: Ecological information**

12.1. Toxicity			
Ecology - general :	Not classified.		
Talc (14807-96-6)			
LC50 fish	89581.02 mg/I - 96 Hours (freshwater fish, QSAR)		
EC50 Daphnia	36812.36 mg/l - 48 Hours (freshwater invertebrates, QSAR)		
LC50 fish 2	110000 mg/l - 96 Hours (marine water fish, QSAR)		
EC50 96h - Algae [1]	7202.7 mg/l - 96 Hours (freshwater algae, QSAR)		
NOEC, marine water fish, acute	5 979.72 mg/l (30 days, QSAR)		
NOEC, marine water fish, Chronic	1 412.65 mg/l (30 days, QSAR)		
NOEC, freshwater invertebrates, Chronic	1 459.80 mg/l (30 days, QSAR)		
NOEC, freshwater algae, Chronic	918.80 mg/l (30 days, QSAR)		
12.2. Persistence and degradability			
Sericron® Talc			
Persistence and degradability	Not relevant for inorganic substances.		
Talc (14807-96-6)			
Persistence and degradability	Not relevant for inorganic substances.		
12.3. Bioaccumulative potential			
Sericron® Talc			
Bioaccumulative potential Not relevant for inorganic substances.			
Talc (14807-96-6)			
BCF - Fish [1]	3.162 l/kg (Whole body, Freshwater, QSAR)		
Log Pow	-9.4 (25 °C, pH 7), (QSAR)		
Bioaccumulative potential	No potential for bioaccumulation.		

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.4. Mobility in soil		
Sericron® Talc		
Ecology - soil	No information available.	
Talc (14807-96-6)		
Ecology - soil	Insoluble in water.	
12.5. Other adverse effects		

No additional information available

SECTION 42: Dispessel considerations	
SECTION 13: Disposal considerations	
13.1. Disposal methods	
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
SECTION 14: Transport information	
In accordance with DOT / TDG / IMDG / IATA	
14.1. UN number	
Not regulated for transport	
14.2. UN proper shipping name	
Proper Shipping Name (DOT)	: Not applicable
Proper Shipping Name (TDG) Proper Shipping Name (IMDG)	: Not applicable : Not applicable
Proper Shipping Name (IATA)	: Not applicable
14.3. Transport hazard class(es)	
DOT	
Transport hazard class(es) (DOT)	: Not applicable
TDG	
Transport hazard class(es) (TDG)	: Not applicable
IMDG	
Transport hazard class(es) (IMDG)	: Not applicable
ΙΑΤΑ	
Transport hazard class(es) (IATA)	: Not applicable
14.4. Packing group	
Packing group (DOT) Packing group (TDG)	: Not applicable : Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable
14.5. Environmental hazards	
Other information	: No supplementary information available.

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.6. Special precautions for user

#### DOT

No data available

## TDG

No data available

#### IMDG

No data available

### IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

Sericron® Talc				
SARA Section 311/312 Hazard Classes	Health hazard - Carcinogenicity Health hazard - Specific target organ toxicity (single or repeated exposure)			
Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):				
Name	CAS-No.	Listing	Commercial status	Flags
Talc	14807-96-6	Present	Active	
Chlorite-group minerals	1318-59-8	Not present	-	
Dolomite	16389-88-1	Present	Active	
Quartz	14808-60-7	Present	Active	
Magnesite	7760-50-1	Not present	-	
Calcite	1317-65-3	Present	Active	

### 15.2. International regulations

### CANADA

### Talc (14807-96-6)

Listed on the Canadian DSL (Domestic Substances List)

### Chlorite-group minerals (1318-59-8)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

### Dolomite (16389-88-1)

Listed on the Canadian NDSL (Non-Domestic Substances List)

### Quartz (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **EU-Regulations**

No additional information available

#### **National regulations**

#### **Sericron® Talc**

All naturally occuring components of this product are automatically included in the USEPA TSCA inventory list per 4- CFR 710.4 (b). All other components are on the USEPA TSCA inventory list

Generally acceptable for use in vanilla powder and vanilla-vanillan powder under food standards 21 CFR 169.179 and 169.182 Generally Recognized As Safe as an anti-caking agent in table salt up to 2% (21 CFR 182.2437)

Generally approved for use as a pigment or colorant under 21 CFR 175.300, 175.380, 175.390, 176.170, 177.1210, 177.1350, 177.1460

Generally approved for use as a colorant only as components of paper and paperboard in contact with aqueous fatty foods (21 CFR 176.170)

### Talc (14807-96-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer) Listed on INSQ (Mexican National Inventory of Chemical Substances)

### 15.3. US State regulations

This product can expose you to , which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Talc(14807-96-6)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Quartz(14808-60-7)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Calcite(1317-65-3)	U.S New Jersey - Right to Know Hazardous Substance List

### **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations			
Revision date	: 2/15/2023		
Data sources	: US OSHA HazCom (GHS) 25 May 2012.		

Full text of H-phrases		
H335	May cause respiratory irritation.	
H350	May cause cancer.	
H370	Causes damage to organs.	

Abbreviations and acronyms		
ACGIH (American Conference of Government Industrial Hygienists)		
	ATE (Acute Toxicity Estimate)	

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

eviatio	ons and acronyms
	CAS (Chemical Abstracts Service) number
	DNEL (Derived No Effect Level)
	EC50 (Effective Concentration 50%)
	IARC (International Agency for Research on Cancer)
	IATA (International Air Transport Association)
	IMDG (International Maritime Dangerous Goods Code)
	IMO (International Maritime Organisation)
	LC50 (Lethal Concentration 50%)
	LD50 (Lethal Dose 50%)
	OECD (Organisation for Economic Co-operation and Development)
	OSHA (Occupational Safety and Health Administration) (US)
	PBT (Persistent, Bioaccumulative and Toxic)
	PNEC (Predicted No Effect Concentration)
	QSAR (Quantitative Structure-Activity Relationship)
	STEL (Short Term Exposure Limit)
	TSCA (Toxic Substances Control Act) (US)
	TWA (Time Weighted Average)
	UNxxxx (Number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods)
	vPvB (very Persistent and very Bioaccumulative)

NFPA health hazard	<ul> <li>: 1 - Materials that, under emergency conditions, can cause significant irritation.</li> <li>: 0 - Materials that will not burn under typical fire conditions, including</li> </ul>
	intrinsically noncombustible materials such as concrete, stone, and sand.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.
Hazard Rating	
Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
	: * - Chronic (long-term) health effects may result from repeated overexposure
Flammability	: 0 Minimal Hazard - Materials that will not burn
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
Personal protection	: E - Safety glasses, Gloves, Dust respirator

# Indication of changes:

Section	Changed item	Change	Comments
1	Identification	Modified	No additional information available
3	Composition/information on ingredients	Modified	No additional information available
7	Handling and storage	Modified	No additional information available

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Neither Minerals Technologies Inc., nor any of its affiliates ("MTI") shall be responsible for the use of information, product, method, or apparatus herein presented ("Information"), and you must make your own determination as to its suitability and completeness for your own use, for the protection of the environment, and for health and safety purposes. You assume the entire risk of relying on this information. In no event shall MTI be responsible for damages of any nature whatsoever resulting from the use of or reliance upon this information. By providing this information, MTI neither can nor intends to control the method or manner by which you use, handle, store, or transport MTI products. Nothing herein shall be construed as a recommendation or license to use any Information that conflicts with any patent, trademark or copyright. Material Safety Data Sheets providing safety precautions that should be observed in handling and storing MTI products are available upon request. You should obtain and review the available material safety information before handling any of these products.

MTI MAKES NO PRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE REGARDING THIS INFORMATION, AND NOTHING HEREIN WAIVES ANY CONDITIONS OF SALE. This information could include technical inaccuracies or typographical errors. Changes are periodically added to the information herein; these changes will be incorporated in revisions of the information. MTI may make improvements and/or changes in the product(s) described in this information at any given time.