

FEATURES

- ▶ Narrow particle size distribution
- ▶ Nano particle size
- ▶ Process controlled top size
- ▶ Surface treated for improved dispersion

BENEFITS

SEALANTS

- ▶ Improved sag and slump properties
- ▶ Improved viscosity and thixotropy
- ▶ Improved adhesion

PLASTICS

- ▶ Improved impact strength
- ▶ Higher gloss vs. other fillers
- ▶ Minimized impact modifier loading
- ▶ Reduced process aid loading for overall reduced cost

ULTRA-PFLEX® & ULTRA-PFLEX® 100

Precipitated Calcium Carbonate

Product Description

ULTRA-PFLEX® and ULTRA-PFLEX® 100 are surface treated, premium quality, engineered nano particle precipitated calcium carbonate produced in Adams, Massachusetts.

ULTRA-PFLEX® ultrafine PCC products are used in PVC plastisol, MS Polymer, silicone, and polyurethane sealant systems. They provide rheological properties, including thixotropy and viscosity control resulting in improved sag and slump characteristics of the sealant. The multi-functional aspects of ULTRA-PFLEX® products provide the formulator with a unique tool which help solve demanding performance problems, while offering significant cost savings potential.

In plastics, ULTRA-PFLEX® products impart improved performance properties to rigid PVC products. The nano particle size and narrow distribution deliver excellent impact properties, extrusion performance, improved surface appearance, and gloss. Typical applications include window profiles, pipe fittings, injection molded parts for decorative applications, and small dimensions parts with critical performance requirements.

Typical Physical Properties*

	ULTRA-PFLEX	ULTRA-PFLEX 100
Average Primary Particle Size (microns)	0.07	0.07
Specific Gravity	2.51	2.57
Dry Brightness (Hunter Y, Rd Value)	96.5	97
Bulk Density (grams/cc)	.31	.33
Tap Density (grams/cc)	.49	.54
Surface Area (meters ² /gram)	21	21
Paste Viscosity, cps *Brookfield @ 20rpm, 35% filler in DINP	8,214	13,260
Thixotropy *Concentric Cylinder 35% filler in DINP	-61	-435


*Values listed are typical, not to be considered as specifications of the product.

Chemical Properties

Calcium Carbonate	98%
Moisture	<0.5%

ULTRA-PFLEX® & ULTRA-PFLEX® 100

Precipitated Calcium Carbonate



SHIPPING INFORMATION

Ultra-Pflex® & Ultra-Pflex 100
ship from Adams, MA

Product is available in 50 lb.
bags, supersacks, and bulk.

For availability and minimum
order quantity, contact
customer service.

SALES OFFICES

Adams, MA
877-684-7627

Bethlehem, PA
800-801-1031

www.mineralstech.com

The information provided may not be used for any purpose other than to identify prospective products consumers may be interested in purchasing. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use. All information given and recommendations made herein are based upon our research and are believed to be accurate, but no guarantee, either expressed or implied, is made with respect thereto or with respect to the infringement of any patent. SMI MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. Inconsistent terms and conditions contained in Buyer's purchase order shall not be binding on SMI unless reflected in writing signed by SMI's representative.